

DIGITUS Cabo de conexão USB-C 3.1 Gen2, USB-C para USB-C

AK-300139-010-S
EAN 4016032426011



USB Type-C connection cable, type C to C M/M, 1.0m, Gen2, 5A, 10GB, 3.1 Version, CE, BI

Para a ligação de dispositivos USB externos (com conector fêmea C, p. ex., computador, Tablet ou Smartphone) a um anfitrião USB (p. ex. computador, computador portátil). Taxa de transferência de dados até 10 Gbps (Superspeed+).

Um cabo para troca de dados, carregamento e diversão com vídeo/áudio.

- USB 3.1 com taxa de transferência de dados até 10 Gbps, Superspeed+
- Suporta alimentação elétrica até 20 V/5 A, 100 W
- Suporta a especificação USB PD (Power delivery).
- Suporta vídeo/áudio até 4K (4096 x 2304, 30Hz)
- Suporta sinais de vídeo/áudio DisplayPort
- A resolução possível depende do dispositivo de origem

- Suporte de dispositivo em DP 1.2: canal único 5,4 Gbps, resolução máxima: 4K@60Hz
- Suporte de dispositivo em DP1.4: canal único, 8,1 Gbps, resolução: 8K@60Hz
- AWG: 30
- Color cable: black
- Color connector: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	11.80	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	0.59	40.00	35.00	7.60	10,640.00
Packaging Unit Single	1	0.06	25.00	13.50	1.30	438.75
Net single without Packaging	1	0.05	10.00	10.00	1.30	0.00

More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com