

# DIGITUS Соединительный кабель USB-C 3.1 Gen2, USB-C к USB-C

AK-300139-010-S  
EAN 4016032426011



**USB Type-C connection cable, type C to C M/M, 1.0m, Gen2, 5A, 10GB, 3.1 Version, CE, BI**

Для подключения внешних USB-устройств (с гнездом типа C, например, ПК, планшета или смартфона) к USB-хосту (например, к ПК, ноутбуку). Скорость передачи данных до 10 Гбит/с (Superspeed+).

**Кабель для передачи данных, зарядки и воспроизведения видео-/аудиоконтента.**

- Скорость передачи данных по USB 3.1 до 10 Гбит/с, Superspeed+
- Поддерживает энергоснабжение до 20 В/5 А, 100 Вт
- Поддерживает спецификацию USB PD (подача мощности).
- Поддержка видео-/аудиосигналов до 4K (4096 x 2304, 30 Гц)

- Поддерживает видео-/аудиосигналы стандарта DisplayPort

**Attributes**

- AWG: 30
- Color cable: black
- Color connector: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	200	11.80	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	0.59	40.00	35.00	7.60	10,640.00
Packaging Unit Single	1	0.06	25.00	13.50	1.30	438.75
Net single without Packaging	1	0.05	10.00	10.00	1.30	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)