

DIGITUS HDMI KVM IP Extender Set

DS-55202
EAN 4016032429432



HDMI KVM Extender, 120 m, Full HD, 1080p over network cable (Cat 5, 5E, 6),

The Digitus HDMI KVM extender set consists of a sender unit (local location) as well as a receiver unit (remote location). The HDMI signal can be extended by means of a network cable (CAT 6, 5e, 5) up to a maximum distance of 120m. The HDMI signal can also be extended to an unlimited distance via the existing network infrastructure (via IP connection). The highest supported video resolution is 1080p / 60 Hz. It also makes convenient access on a computer (mouse and keyboard) possible via the USB ports on the receiver unit. It is perfectly suited to industrial, commercial and public applications.

Extends the HDMI signal to up to 120 m and offers the possibility of controlling the keyboard and mouse via USB on the receiver unit

- Extends the maximum length for HDMI cable to up to 120 m via a simple network cable
- Extension of the signal (unlimited distance) over the existing local network infrastructure (over IP connection)
- Highest supported video resolution: 1080p / 60 Hz
- Supports KVM function - convenient control of mouse and keyboard via USB on the receiver unit
- Supports LAN-standard 802.3 Ethernet 10/100/100 Mbps
- LED activity indicator for function, keyboard and mouse
- Transmission lengths: 120 m (CAT6), 100 m (CAT5e), 80 m (CAT5)
- Video bandwidth: < 70 Mbps
- Video latency: 70 ms

- Audio support PCM (44.1KHz, 48KHz)
- USB keyboard and mouse support
- Supports UTP/STP CAT 5/ 5e/6/7 network cables in accordance with IEEE-568B standard
- Plug & Play, no additional software required - driver CD only needed as long as there is no mouse and keyboard function
- Electricity consumption: < 3.5 W (TX or RX)
- Operating temperature: 0 ~ 60° C
- Ambient temperature: -20 ~ 70° C
- High quality aluminum casing
- Dimensions: L 11.0 x W 9.0 x H 2.6 cm
- Color: black
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Category: CAT 5e
- Distance: 80 m
- KVM: yes
- PoE (Power over Ethernet): no
- Transmission technology: IP
- Video connection ports: HDMI

Package contents

- 1x HDMI Extender transmitter unit
- 1x HDMI Extender receiver unit
- 2x Power supply unit: DC 5V/1A
- 1x Instruction manual
- 1x CD (USB Driver Software)

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 10 | 7.40 | 36.70 | 25.50 | 42.00 | 39,305.70 |
| Packaging Unit Inside | 1 | 0.74 | 24.00 | 17.60 | 8.00 | 3,379.20 |
| Packaging Unit Single | 1 | 0.74 | 24.00 | 17.60 | 8.00 | 3,379.20 |
| Net single without Packaging | 1 | 0.30 | 11.00 | 9.00 | 2.60 | 0.00 |

More images:

