

DIGITUS CAT 6 Industrial Coupler, shielded

DN-IND-C6-C
EAN 4016032429623



CAT 6 STP industrial bulkhead coupler, IP67 with dust cap

CAT 6 STP industrial bulkhead coupler, IP67,with dust cap

Best performance and link quality for your network. Ideal for industrial applications.

- Main body & dust cap: PBT+GF, UL94V-0
- Shielded case: Brass, nickel plated
- Coupler housing: ABS, UL94V-0
- Module contacts: Phosphor bronze, 50 μ gold plated
- Insertion life: 750 mating cycles with FCC compliant 8P plug

- Contact force: 100 g with FCC compliant 8P plug
- Plug retention force: 11 LBF min.
- Operating temperature range: -10 °C up to +60 °C
- Storage temperature range: -40 °C up to + 68 °C
- Humidity: 10%~90% RH
- Insulation resistance: 500 MΩ
- Dielectric withstanding voltage: 1000 V AC
- DC current rating: 1.5 Amps.
- DC resistance: 0.1 Ω
- Contact resistance: 20m Ω

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	320	11.52	17.00	30.00	10.00	5,100.00
Packaging Unit Inside	1	0.04	3.00	6.50	2.00	39.00
Packaging Unit Single	1	0.04	3.00	6.50	2.00	39.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com