

DIGITUS CAT 6A Field Termination Coupler, 500 MHz

DN-93909
EAN 4016032431268



Field Termination Coupler CAT 6A, 500 MHz for AWG 22-26, fully shielded, keyst. design, 26x35x80

The DIGITUS Professional Field Termination Coupler is used for connecting or extending of twisted pair cables.

- Transmission properties: Category 6A, Class EA
- Area of application: Up to 500 MHz, 10GBase-T

- Suitable for cables with AWG 22-26 diameter
- Shell: Zinc alloy
- Contacts: Nickel-plated
- shielded
- Keystone Design
- 1 to 1
- Operating temperature: -10 °C to +60 °C

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 300 | 11.50 | 34.00 | 24.00 | 28.00 | 22,848.00 |
| Packaging Unit Inside | 10 | 0.38 | 15.00 | 14.00 | 5.00 | 1,050.00 |
| Packaging Unit Single | 1 | 0.04 | 9.00 | 8.00 | 3.00 | 216.00 |
| Net single without Packaging | 1 | 0.04 | 9.00 | 8.00 | 3.00 | 0.00 |

More images:



