

DIGITUS Displayport connection cable, DP, w/ amp.

AK-340105-150-S
EAN 4016032433712



Displayport Connection Cable, Type DP, w/ amp. M/M, 15.0m, w/lock, UHD 4K, DP 1.2, gold, bl

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

A/V connection over long distances without signal loss

- Supports video format: 4K/2K@24Hz, 4K/2K@30Hz or 4K/2K@60Hz
- Supported video resolution: 4K (3840x2160)@60Hz and Full HD (1920x1080)@120Hz
- No external power supply required
- Secure and reliable connection thanks to the plug lock
- Integrated, active signal amplifier
- Supported transmission modes: RBR, HBR, HBR2
- Maximum bandwidth: 21.6 Gbps
- HBR version/transfer mode: HBR2 (5.40 Gbit/s per lane)
- HDCP version: HDCP 1.3

Attributes

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: gold-plated
- DisplayPort standard: DisplayPort 1.2
- HDTV Standard: Ultra HD 4K
- Hoods: plastic
- Interlock: Snap fastener
- Wire material: CU
- Length: 15 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	7	10.30	38.10	31.10	30.20	35,784.30
Packaging Unit Inside	1	1.47	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.47	33.50	33.50	6.50	7,294.62
Net single without Packaging	1	1.36	22.00	22.00	6.50	0.00

More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com