


# DIGITUS Переходной кабель DisplayPort, DP – HDMI типа A

AK-340303-030-S  
EAN 4016032438601



**DisplayPort adapter cable, DP - HDMI type A M/M, 3.0m, w/lock, DP 1.2\_HDMI 2.0, 4K/60Hz,CE, bi**

Этот высокоскоростной цифровой аудио-/видеокабель с поддержкой HD используется для подключения ПК или ноутбука к мониторам с интерфейсом HDMI.

**Согласующий соединительный кабель Plug-and-Play не требует электропитания от внешних источников и позволяет не использовать адаптер.**

- Поддерживает характеристики HDMI 2.0
- Поддерживает 4K/2K при 60 Гц
- Поддерживает 3D с разрешением 1080p
- Поддерживает HDCP и DPCP
- Assortment: DisplayPort Cables
- AWG: 28

- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: HDMI type A, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 3 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

**Logistics**

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	40	9.70	25.00	35.00	55.00	48,125.00
Packaging Unit Inside	10	2.43	10.00	24.00	38.00	9,120.00
Packaging Unit Single	1	0.24	3.00	18.00	18.00	972.00
Net single without Packaging	1	0.00	2.00	17.00	17.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)