

# DIGITUS HDMI Extender Set, Full HD, 50 m

DS-55100-1  
EAN 4016032439929



### HDMI Extender Set, 50 m over network cable (CAT 6/6a/7), EDID, 1x HDMI loop out, FHD, 1080p

The Digitus HDMI Extender Set, Full HD offers an extender solution of up to 50 m for the highest demands. It is used to transmit digital video and audio signals to a maximum length of up to 50 m. The highest supported video resolution is 1080p / 60Hz. The transmitter unit features an EDID switch, which can be used to regulate resolution and audio format of the output signal. The transmitter also has an HDMI Loop Out Port, which allows you to connect a local monitor. Thanks to PoC (Power over Cable) support, it is only the transmitter unit that needs to be powered. The package includes two bidirectional infrared units (transmitter, receiver), which can be used for the remote control of the connected input source.

#### Extends the maximum length for HDMI cables to up to 50 m whereby only a simple network cable is used between a sender and a receiver unit

- Extends the maximum length for HDMI cable to up to 50 m via a simple network cable
- Highest supported video resolution: 1080p / 60 Hz
- Supports CAT 6, CAT 6A, CAT 7 network cables
- EDID Switch - Allows you to set resolution and audio format on the transmitter unit
- HDMI Loop Out - Allows you to connect a local monitor to the transmitter unit

- Supports PoE (Power over Ethernet) - thus no power supply is required for the receiver unit
- Supports HDCP 1.2a
- Bandwidth: 4.95 Gbps
- Color depth: 8 bit
- Supports uncompressed audio signals such as LPCM
- Metal casing
- Compact size, simple use and installation
- Power supply unit: DC 5V/2A
- Dimensions (1x unit): L 7.2 x W 6.70 x H 2.3 cm
- Color: black
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Category: CAT 6
- Distance: 50 m
- KVM: no
- PoE (Power over Ethernet): yes
- Video connection ports: HDMI

#### Package contents

- 1x HDMI Extender transmitter unit
- 1x HDMI Extender receiver unit
- 1x Power supply unit: DC 5V/2A
- 1x IR transmitter unit
- 1x IR receiver unit
- 1x Instruction manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	20	23.00	42.50	31.50	42.00	56,227.50
Packaging Unit Inside	1	1.15	20.00	15.00	8.00	2,400.00
Packaging Unit Single	1	1.15	20.00	15.00	8.00	2,400.00
Net single without Packaging	1	0.14	7.20	6.70	2.70	0.00

More images:

