

DIGITUS Gigabit Ethernet PoE Injector, 802.3af, 15,4 W

DN-95102-1
EAN 4016032441120



Gigabit Ethernet PoE Injector, 802.3af Power Pins:4/5(+),7/8(-), 15.4W

The Digitus PoE Injector minimizes your cabling when installing PoE compatible devices such as IP network cameras. Only the Ethernet cable is used for the data feed and power supply for the devices. This eliminates the need to install a separate power line, and you can extend your network where there are no power outlets or power lines. The injector is fully compliant with the IEEE 802.3af PoE standard and delivers output power of up to 15.4W.

Minimize cabling for wireless APs, IP phones, or any other PoE compatible device!

- Meets the 802.3af PoE standard
- 48V output voltage, 15.4 Watt
- RJ45 LAN input
- LAN (RJ45) output, power supply via pin: 4/5(+), 7/8(-)

- Cable connection: 10/100/1000 Mbps
- The output has a current limit, a short-circuit protection and an automatic terminal device detection and classification
- Power consumption: 1.6W max.
- Power supply: 100-240V AC, 0.8A
- Operating temperature: -5°C - 45°C
- Dimensions (mm): 134(L) x 56(W) x 33(H)
- PoE standard: IEEE802.3af (PoE)
- Ethernet speed: Gigabit
- Industrial usage: no

Package contents

- PoE Injector
- Quick start guide
- Power cord

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	17.26	47.50	31.50	34.00	50,872.50
Packaging Unit Inside	1	0.86	16.50	5.00	13.80	1,138.50
Packaging Unit Single	1	0.86	16.00	14.00	5.00	1,108.00
Net single without Packaging	1	0.70	13.00	6.00	3.00	0.00

More images:



