

DIGITUS Conversor multimédia 10 Gigabit

DN-82211
EAN 4016032441175



10 Gigabit Ethernet Media Converter, SFP supports 1G, 2.5G, 5G and 10G, open slot

Os Conversores multimédia da DIGITUS® são a solução ideal para a migração de sinais de rede de fibra e de cabo de cobre. A partir de agora, é possível aceder à tecnologia de fibra e transferir os sinais de rede ao longo de vários quilómetros sem ter de substituir toda a infra-estrutura de rede. A nossa grande variedade de produtos corresponde às suas necessidades individuais. O funcionamento intuitivo garante uma instalação fácil e rápida. Os anos de experiência e a grande variedade de produtos permitem que a DIGITUS® se torne num parceiro fiável para a sua engenharia de rede.

A solução de conversão ideal para transmissão de dados óticos

- 1 x RJ45 / 1 x SFP
- Suporta 1000Base-T para 1000Base-X, 2,5G Base-T para 2,5G Base-X, 5G Base-T para 5G Base-R e 10G Base-T para 10G Base-R
- Alcance até 80km
- Converte sinais de rede baseados em cabo em sinais de fibra ótica
- Suporta tomada de pressão e controlo de largura de banda em cada porta

- Tecnologia Store-and-Forward para uma transferência de dados otimizada
- Auto MDI/Função MDI-X
- LED de diagnóstico sobre o estado e monitorização de atividade
- Temperatura de funcionamento: 0 até 55°C
- Conversor Standalone com fonte de alimentação externa
- Connector 1: RJ45
- Connector 2: SFP
- Mode: Depending on module
- Distance (km): Depending on module
- Industrial usage: no
- Broadcasting Mode: Unidirectional
- PoE injector: yes
- Ethernet speed: 10 Gigabit

Package contents

- Conversor multimédia 10 Gigabit
- Peso: 20 g
- Fonte de alimentação

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	8.00	40.00	26.00	34.00	35,360.00
Packaging Unit Inside	1	0.40	24.00	13.00	6.00	1,872.00
Packaging Unit Single	1	0.40	24.00	13.00	6.00	1,872.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Product Number	SKU Code	Name	Connector	Distance	Medium	Wavelength	Operating Temperature	Accessories
084-00001	4000000001	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00002	4000000002	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00003	4000000003	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00004	4000000004	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00005	4000000005	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00006	4000000006	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00007	4000000007	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00008	4000000008	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00009	4000000009	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00010	4000000010	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00011	4000000011	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00012	4000000012	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00013	4000000013	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00014	4000000014	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00015	4000000015	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00016	4000000016	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00017	4000000017	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00018	4000000018	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00019	4000000019	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00020	4000000020	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00021	4000000021	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00022	4000000022	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00023	4000000023	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00024	4000000024	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00025	4000000025	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00026	4000000026	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00027	4000000027	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00028	4000000028	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00029	4000000029	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00030	4000000030	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00031	4000000031	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00032	4000000032	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00033	4000000033	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00034	4000000034	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00035	4000000035	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00036	4000000036	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00037	4000000037	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00038	4000000038	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00039	4000000039	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00040	4000000040	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00041	4000000041	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00042	4000000042	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00043	4000000043	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00044	4000000044	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00045	4000000045	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00046	4000000046	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00047	4000000047	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00048	4000000048	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	
084-00049	4000000049	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	-5 to +55°C	
084-00050	4000000050	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	-5 to +55°C	



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com