

DIGITUS Conversor multimédia 10 Gigabit

DN-82211
EAN 4016032441175



10 Gigabit Ethernet Media Converter, SFP supports 1G, 2.5G, 5G and 10G, open slot

Os Conversores multimédia da DIGITUS® são a solução ideal para a migração de sinais de rede de fibra e de cabo de cobre. A partir de agora, é possível aceder à tecnologia de fibra e transferir os sinais de rede ao longo de vários quilómetros sem ter de substituir toda a infra-estrutura de rede. A nossa grande variedade de produtos corresponde às suas necessidades individuais. O funcionamento intuitivo garante uma instalação fácil e rápida. Os anos de experiência e a grande variedade de produtos permitem que a DIGITUS® se torne num parceiro fiável para a sua engenharia de rede.

A solução de conversão ideal para transmissão de dados óticos

- 1 x RJ45 / 1 x SFP
- Suporta 1000Base-T para 1000Base-X, 2,5G Base-T para 2,5G Base-X, 5G Base-T para 5G Base-R e 10G Base-T para 10G Base-R
- Alcance até 80km
- Converte sinais de rede baseados em cabo em sinais de fibra ótica
- Suporta tomada de pressão e controlo de largura de banda em cada porta

- Tecnologia Store-and-Forward para uma transferência de dados otimizada
- Auto MDI/Função MDI-X
- LED de diagnóstico sobre o estado e monitorização de atividade
- Temperatura de funcionamento: 0 até 55°C
- Conversor Standalone com fonte de alimentação externa

Attributes

- Connector 1: RJ45
- Connector 2: SFP
- Mode: Depending on module
- Distance (km): Depending on module
- Industrial usage: no
- Broadcasting Mode: Unidirectional
- PoE injector: yes
- Ethernet speed: 10 Gigabit

Package contents

- Conversor multimédia 10 Gigabit
- Peso: 20 g
- Fonte de alimentação

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	8.00	40.00	26.00	34.00	35,360.00
Packaging Unit Inside	1	0.40	24.00	13.00	6.00	1,872.00
Packaging Unit Single	1	0.40	24.00	13.00	6.00	1,872.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Product Name	SKU Code	Name	Connector	Distance	Medium	Wavelength	Operating Temperature	Accessories
Media Converter	400000000	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000001	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000002	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000003	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000004	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000005	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000006	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000007	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000008	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000009	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000010	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000011	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000012	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000013	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000014	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000015	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000016	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000017	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000018	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000019	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000020	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000021	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000022	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000023	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000024	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000025	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000026	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000027	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000028	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000029	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000030	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000031	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000032	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000033	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000034	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000035	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000036	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000037	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000038	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000039	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000040	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000041	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000042	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000043	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000044	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000045	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000046	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000047	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000048	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	
Media Converter	400000049	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1550nm	0 to 40°C	
Media Converter	400000050	10/100Mbps	10/100Mbps RJ45	2 km	Fiber	1310nm	0 to 40°C	



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com