

DIGITUS 4K HDMI Switch, 5x1

DS-45317

EAN 4016032442493



4K Highspeed HDMI 2.0 Switch, 5x1 UHD 4K*2K@60Hz, Full 3D, aluminum housing, black

The Digitus 4K HDMI Switch 5x1 makes it possible to change conveniently between 5 HDMI input sources (DVD/Blu-Ray Player, game consoles, streaming boxes/sticks, digital receivers, etc.) via remote control, intelligent automatic recognition or alternatively by switching the switch itself. The hassle of reconnecting cables is a thing of the past. Thanks to Ultra HD 4K (60 Hz) support, experience your media content in brilliantly sharp resolution.

Discover the full potential of UHD - it supports 4K2K (60Hz)

- Convenient switching between up to five HDMI sources without the burdensome reconnection
- Discover the full potential of UHD - it supports 4K2K (60Hz)
- Resolutions: 4K (60Hz), 4K (30Hz), 1080p, 1080i, 720p, 576p, 576i, 480p, 480i
- Supports HDCP 2.2
- Supports 600 MHz (max.) bandwidth - 6 Gbit/s (max.) transfer rate per channel

- Premium aluminum housing
- Supports HDTV
- Supports 21:9 wide-angle cinema format
- Supports High Dynamic Range (HDR) video
- Supports Deep Color: 12 bit color depth per channel
- Standard HDMI/High Speed HDMI compliant
- Supports compressed audio formats, e.g. DTS digital, Dolby Digital (incl. DTS-HD and Dolby True HD)

Attributes

- HDTV Resolution max.: 3840 x 2160 Pixel, 60Hz
- HDTV Standard: Ultra HD 4K
- Signal input: HDMI

Package contents

- UHD HDMI Switch, 5x1
- Remote control
- Power supply (5V/1A)
- User manual

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	4.90	51.00	25.00	23.00	29,325.00
Packaging Unit Inside	1	0.49	20.00	19.50	3.00	1,170.00
Packaging Unit Single	1	0.49	20.00	19.50	3.00	1,170.00
Net single without Packaging	1	0.21	15.80	6.00	1.80	0.00

More images:



Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com