


# DIGITUS Cabo SFP+ 10G 5m DAC

DN-81224-01  
EAN 4016032446040



### SFP+ 10G DAC Cable 5m AWG 24, HP HPE compatible

Os cabos SFP+ 10G DAC Digitus® consistem na ligação ideal entre a área de comutação e de rede dorsal. Para a utilização de cabos SFP+ 10G DAC são suportados os seguintes volumes de transmissão de dados e aplicações: 10G Ethernet (10,21 Gbps), Canal de Fibra 10G (10,52 Gbps), Canal de Fibra 8G (8,5 Gbps), Canal de Fibra 4G (4,25 Gbps), Canal de Fibra 2G (2,125 Gbps), Canal de Fibra 1G (1,0625 Gbps), Gigabit Ethernet (1,25 Gbit / s), Opção CPRI 2,3,5,6,7,8, OBSAI RP3 x 2, RP3 x 4, RP x 8. Os cabos SFP+ 10G DAC são compatíveis com Hewlett Packard (HP) H3C.

### Amplie as suas ligações de cobre

- Cabo AWG 24 Twinax
- Distância máxima de 5 m
- Volume de transmissão de dados suportado de 1,0625-10,52 Gbps

- Aplicações suportadas: 10G Ethernet (10,21 Gbps), Canal de Fibra 10G (10,52 Gbps), Canal de Fibra 8G (8,5 Gbps), Canal de Fibra 4G (4,25 Gbps), Canal de Fibra 2G (2,125 Gbps), Canal de Fibra 1G (1,0625 Gbps), Gigabit Ethernet (1,25 Gbit / s), Opção CPRI 2,3,5,6,7,8, OBSAI RP3 x 2, RP3 x 4, RP x 8
- Marcas compatíveis: Compatível com Hewlett Packard (HP) HPE
- Suporta DDM / DOM
- Gama de temperatura: 0 - -70 ° C
- Ligações: SFP +
- Potência: Tensão de alimentação de + 3,3V
- Potência absorvida: 0,5W
- Tipo de transmissor: DAC
- AWG: 24
- Length: 5 m
- DDM Support: no
- Manufacturer compatibility: HP

### Package contents

- Cabo SFP+ 10G 5m DAC
- Peso: 20 g

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	1.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.02	32.00	32.00	4.00	4,096.00
Packaging Unit Single	1	0.02	32.00	32.00	4.00	4,096.00
Net single without Packaging	1	0.26	5.80	1.40	1.10	0.00

### Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.

- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)