

# DIGITUS HP-compatible SFP+ 10G MM 850nm 300m with DDM

DN-81200-01  
 EAN 4016032446149



**10G SFP+ Module, Multimode, DDM, HP-compatible LC Duplex Connector, 850nm, up to 300m, HP**

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

**The plug and play fiber connection**

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 850nm

- Transmission Power: Minimum -5 dBm, Maximum -1 dBm
- Empfangssensitivität: Minimum -11,5 dBm
- For a distance of up to 0.3km
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Mode: Multimode
- Connector: LC
- Distance (km): 0.3
- Wavelength: 850 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: 10 Gigabit

**Package contents**

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	0.80	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.04	1.50	9.00	3.00	40.50
Packaging Unit Single	1	0.04	12.00	9.30	3.20	357.12
Net single without Packaging	1	0.03	5.60	1.40	1.10	0.00

More images:



SFP Modules						
Part Number	SKU Code	Speed	Distance	Connector	Mounting	Operating Temperature
DA-PA01	4010000000001	10 Gbps	10 km	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA02	4010000000002	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA03	4010000000003	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA04	4010000000004	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA05	4010000000005	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA06	4010000000006	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA07	4010000000007	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA08	4010000000008	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA09	4010000000009	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA10	4010000000010	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA11	4010000000011	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA12	4010000000012	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA13	4010000000013	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA14	4010000000014	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA15	4010000000015	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA16	4010000000016	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA17	4010000000017	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA18	4010000000018	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA19	4010000000019	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA20	4010000000020	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA21	4010000000021	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA22	4010000000022	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA23	4010000000023	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA24	4010000000024	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA25	4010000000025	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA26	4010000000026	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA27	4010000000027	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA28	4010000000028	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA29	4010000000029	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA30	4010000000030	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA31	4010000000031	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA32	4010000000032	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA33	4010000000033	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA34	4010000000034	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA35	4010000000035	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA36	4010000000036	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA37	4010000000037	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA38	4010000000038	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA39	4010000000039	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA40	4010000000040	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA41	4010000000041	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA42	4010000000042	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA43	4010000000043	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA44	4010000000044	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA45	4010000000045	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA46	4010000000046	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA47	4010000000047	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA48	4010000000048	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA49	4010000000049	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C
DA-PA50	4010000000050	10 Gbps	300m	LC Duplex Plastic	19mm	-40 to 75 °C

