

# DIGITUS USB Type-C Gen2 adapter / converter cable, Type-C to HDMI A

AK-300330-050-S  
EAN 4016032451327



### USB Type-C adapter cable, Type-C to HDMI A M/M, 5.0m, 4K/60Hz, 18GB, bl, gold

The USB Type-C 4K HDMI adapter / converter cable allows a direct connection of TV, monitor or projector to a USB-C device. The adapter / converter cable is a must-have accessory, whether you connect your Notebook privately to a TV or professionally for presentations via an HDMI projector.

**Connect your USB-C device directly to a monitor, TV or beamer - No need of an additional adapter.**

- Your USB-C equipped device must support video (DP alt mode) to work with this adapter / converter cable.

- Video output capability depends on the graphics card of your notebook and the connected monitor. Some screens also limit the available resolution.
- Support up to 4K/2K with 60Hz
- Supports digital transfer of audio signals, stereo
- Data transfer rate up to 18 Gbit/s
- AWG: 26
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 2.0
- Length: 5 m
- USB-C Products: yes

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 20           | 11.40       | 35.00      | 26.00      | 24.00       | 21,840.00       |
| Packaging Unit Inside        | 5            | 2.85        | 19.00      | 20.00      | 27.00       | 5,250.00        |
| Packaging Unit Single        | 1            | 0.57        | 19.00      | 4.00       | 27.00       | 2,052.00        |
| Net single without Packaging | 1            | 0.19        | 17.50      | 4.00       | 15.00       | 0.00            |

### More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)