

DIGITUS Switch de rede Gigabit Ethernet de 8 portas, industrial, não gerido

DN-651108
EAN 4016032454489



Industrial Gigabit Ethernet Switch 8-port, DIN rail, extended temp. range

O Conversor Industrial Gigabit DIGITUS® foi concebido para ambientes agressivos, nos quais fica exposto à humidade, oscilações de temperatura e vibrações. Com uma gama de temperatura de -40°C a 75°C, o Conversor Industrial Gigabit pode ser utilizado sob as condições mais adversas. Assegura uma disponibilidade constante nas áreas altamente sensíveis, tais como de transporte, produção, trânsito e monitorização de segurança. Através do sistema simples de Plug&Play, é possível integrar rapidamente o Conversor Industrial Gigabit no respetivo ambiente. A conectividade Gigabit torna o conversor Industrial Gigabit numa solução flexível e económica para o ambiente industrial.

- 8 x Portas Ethernet 10/100/1000Base-TX
- Reconhecimento automático de cabo – função auto MDI-/ MDI-X
- Normas suportadas: Gigabit Ethernet segundo as normas IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab
- IEEE802.3x controlo de fluxo e pressão de retorno
- Tecnologia Store-and-Forward para uma transferência de dados otimizada
- Detecção/ajuste de velocidade automáticos e Duplex semi/total
- Barramento com 16Gbps
- Suporta endereços MAC até 8K
- Caixa metálica compacta, robusta

- Excelente proteção contra curto-circuitos
- Proteção contra relâmpagos e sobretensão
- Alimentação redundante: 12 a 56V DC, alimentação redundante com função protetora de inversão de conexão
- Temperatura de funcionamento ampliada, -40°C a +85°C
- Ligação de terminal amovível
- Consumo de energia: 5 W
- MTBF: 500.000 h
- EN 50155 (EN 60068-2-6) Vibração
- EN 50155 (EN 60068-2-27) Choque
- EN 50155 (EN 60068-2-32) Queda livre

Attributes

- Number of ports: 8
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: no

Package contents

- Interruptor industrial Gigabit 8 portas
- Peso: 20 g

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	16	12.60	35.00	24.00	56.00	47,040.00
Packaging Unit Inside	16	12.60	35.00	24.00	56.00	47,040.00
Packaging Unit Single	1	0.79	16.50	6.50	21.50	2,305.88
Net single without Packaging	1	0.52	10.50	3.60	14.20	0.00

More images:



Safety notes

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
- The mains cable, power supply unit or plug for the power supply is damaged or worn;
- Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com