

DIGITUS QSFP+ 40G 3 m DAC cable

DN-81309
EAN 4016032464297



QSFP+ 40G 3m DAC cable

Allnet, CISCO, D-Link, Edimax, Etherwan, Fortinet

The DIGITUS® 40G QSFP+ DAC cables are a high-performance, low-power short-range connection solution. They are compliant with the QSFP MSA and IEEE P802.3ba. It uses 4 full duplex channels, with each channel capable of transmitting data at speeds of up to 10.3Gb/s, giving an aggregate rate of 41.2Gb/s. The DIGITUS® 40G QSFP+DAC cables offer increased port density and cost savings in the overall system.

High bandwidth without delays or signal loss

- 3 m maximum distance
- 2.125-41.2 Gbps supported data rate
- Supported applications: 12.5G fibre channel, 10G channel, 8G fibre channel, 4G fibre channel and 2G fibre channel

- Compatible brands: Allnet, CISCO, 3COM, D-LINK, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL
- DDM/DOM support
- Temperature range: 0 to +70 °C
- Connectors: QSFP
- Power: +3.3 V supply voltage
- Power consumption: <1.5 W
- 850 nm wavelength multimode fibre
- DDM Support: no

Package contents

- QSFP+ 40G 3 m DAC cable
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	150	1.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.01	26.00	26.00	2.00	1,352.00
Packaging Unit Single	1	0.01	26.00	26.00	2.00	1,352.00
Net single without Packaging	1	0.15	11.00	1.80	1.30	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com