

DIGITUS Smart PDU, Outlet Monitored & Switched, 1-phase, 32 A, 20 x C13, 4 x C19

DN-95632
EAN 4016032473343



Outlet monitored&switch PDU, Vertical 32A, 20xC13&4xC19, 3m, IEC60309 32A plug

The DIGITUS® Smart PDU offers you the option to remotely monitor the power, voltage, total energy consumption, total power and power factor at the input/output level, while also enabling the control of outlets (switching on/off, sequential switching, rebooting). The limit value can be set for the total current and the alarm warns you about potential system overloads. Monitoring of the operating status is also enabled as well as for the current, energy and power at the circuit breaker level. This makes it possible to efficiently manage and distribute power. The device can be accessed and configured via web, SNMP and Telnet interfaces. With the option of connecting sensors, the unit can comprise a complete environment monitoring system to control the temperature, smoke, humidity and leaks in the racks. Up to five power strips which share the same network connection and IP address can be connected in series. Furthermore, the PDU can easily be integrated into the racks with tool-free installation options.

Optimal PDU solution with remote monitoring options for demanding IT requirements

- Monitoring of input current / voltage / total energy consumption / total power / power factor
- Monitoring of current / power / energy consumption of outlets
- Individual control of outlets
- User-defined sequential delay for switching outputs on/off
- Remote access method: Web interface, HTTP, HTTPS, SNMP (v1 / v2c / v3), Telnet and serial console
- Daisy-chaining of up to five PDUs (including master device)
- Multi-stage user access
- Compatible with temperature/humidity/smoke/leak sensors
- User-defined alarm: E-mail notification & alarm signal if threshold values are exceeded for individual current per outlet, total current, temperature / humidity

- Standard system alarm: If the total nominal power is exceeded; if smoke, water or an open door is detected
- RJ45 connections for Ethernet and serial communication
- USB A port for WLAN access or software upgrade
- Integrated circuit breaker, 2 x 16 A, hydraulic
- Mains cable: 3 x 6.0 mm², IEC60309 32 A plug
- Cable: 3 m
- Max. load: 8,000 W / 250 V AC / 32 A (50/60 Hz)
- Outlets: 20 x C13 outlet, 4 x C19 outlet
- Output power: C13 (10A), C19 (16A)
- 180 degree rotating HD display
- Dimensions (LxWxD): 1850 x 56 x 52 mm
- Temperature range (operation / storage): 0 °C to +45 °C/ -20 °C to +70 °C
- Humidity range (operation / storage): 5% - 95% RH / 5 - 95% RH (non-condensing)
- Maximum height above sea level (operation / storage): 0 - 3,000 m / 0 - 15,000 m
- Color: Black
- Protection type: IP44
- Current: 32 A
- Input Plug: IEC 60309 32A 1ph/N/PE 6h
- Installation: Rack 0U
- Metering: PDU Metering, Outlet Metering
- Outlets: IEC 60320 C13, IEC 60320 C19
- Phase: 1ph
- Power: 7,3 kVA
- Volts: 230 V

Package contents

- 1 x Smart PDU, outlet monitored & switched, 1-phase, 20 x C13, 4 x C19, 3 m cable IEC 60309 32 A plug

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	4	40.00	42.50	216.50	32.00	294,440.00
Packaging Unit Inside	1	10.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	10.00	19.50	214.00	14.50	60,508.50
Net single without Packaging	1	8.50	5.60	185.00	5.20	0.00

More images:

