

DIGITUS 10G SFP+SR 850nm 300m LC DDM Endüstriyel

DN-81212
EAN 4016032476948



10G SFP+SR 850nm 300m LC DDM Endüstriyel 300m LC DDM Endüstriyel

300 m'ye kadar menzil ve <1 W güç tüketimi ile -40 °C ila 85 °C geniş sıcaklık aralığı, DN-81212 SFP+'yı zorlu ortamlarda güvenilir bir alıcı-verici haline getirir.

10Gb/s SFP+SR MM modülü 850nm 300m DDM (endüstriyel kullanılabilirlik)

- LC konektörlü SFP+ muhafazası
- 850nm VCSEL lazer ve PIN fotodetektör
- 2000MHz-km MMF'de 300 m'ye kadar iletim
- 11.3Gbps'ye kadar veri bağlantısı

- Güç kaybı < 1W
- LVPECL uyumlu veri giriş/çıkış arayüzü
- Düşük EMI ve mükemmel ESD koruması
- Lazer güvenlik standardı IEC-60825 uyumlu
- SFF8472 ile uyumlu
- Çalışma sıcaklığı: -40 ~ 85 ° C
- Şu üreticilerle uyumludur: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- DDM Desteği: no

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	10.00	40.00	56.00	26.00	58,240.00
Packaging Unit Inside	1	0.04	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.04	9.30	11.70	3.20	348.19
Net single without Packaging	1	0.03	1.40	5.80	1.10	0.00

More images:

