

# DIGITUS Audio Extension Cable, 3.5 mm jack to 3.5 mm socket

DB-510210-030-S EAN 4016032481300





#### AUX Audio Cable Stereo 3.5mm Male to Female Aluminum Housing ,Gold plated, NYLON Jacket, 3m

The Audio Extension Cable from Digitus with 3.5 mm jack to 3.5 socket is ideally suited for the extension of jack cables. The aluminum housing and nylon mesh ensure ideal exterior protection. The extension cable is suited for all smartphones, notebooks and audio players with a 3.5 mm connection.

## Cable for 3.5 mm jack connection to extend headphone or PC speaker cables.

Extension of 3.5 mm jack cable (AUX)

- Gold-plated plug
- Nylon mesh

#### Attributes

- AWG: 28
- Color cable: black
- Connector 1: 3.5mm stereo plug
- Connector 2: 3.5mm stereo jackConnector surface: gold-plated
- Length: 3 m
- Shielding: Double shielding

| Logistics                    |                 |                |               |               |                |           |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³       |
| Packaging Unit Carton        | 120             | 7.56           | 34.00         | 43.00         | 31.00          | 45,322.00 |
| Packaging Unit Inside        | 1               | 0.06           | 0.00          | 0.00          | 0.00           | 0.00      |
| Packaging Unit Single        | 1               | 0.06           | 11.00         | 11.00         | 3.00           | 363.00    |
| Net single without Packaging | 1               | 0.04           | 10.00         | 10.00         | 2.00           | 0.00      |

### More images:











#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com