

# DIGITUS Voertuig - laadkabel, 5m, type 2 naar type 2

DK-1P32-050  
EAN 4016032481393



### Voertuig - eenfase, 240V, 32A, 5 m Type 2 naar type 2 laadkabel standaard

Met de DK-1P32-050 voertuig-laadkabel kunt u probleemloos elk voertuig met type 2 stekker aansluiten aan openbare laadstations of een wallbox met laadaansluiting. Laadkabels van type 2 zijn gecertificeerd volgens EN 62196-1:2014, EN 62196-2:2017 en beschermingsklasse IP55.

### Type 2 op type 2 laadkabel, IP55 beschermd, 1-fasig, tot 32 A.

- Type: Standaard kabel
- Kabellengte: 5 m
- Bruikbare lengte: 5 m
- Type oplaadkabel: 3 x 6 mm<sup>2</sup> + 1 x 0,75 mm<sup>2</sup>



- Kleur: Zwart
- Jas: TPU
- Stekker: EN 62196-2 Type 2
- Nominale spanning: 230 V
- Nominaal vermogen: 7,4 kW
- Nominale stroom: 32 A
- Aansluitfasen: 1
- Bedrijfstemperatuur: -30~+50
- Beschermingsklasse: IP55 (beschermd tegen waterstralen)

### Package contents

- 5m Voertuig-aansluitkabel type 2
- Snelstartgids

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	5	15.95	63.00	38.00	38.00	90,972.00
Packaging Unit Inside	1	3.19	0.00	0.00	0.00	0.00
Packaging Unit Single	1	3.19	35.00	35.00	15.00	18,375.00
Net single without Packaging	1	2.51	0.00	0.00	0.00	0.00

### More images:





**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)