

DIGITUS Wall Box 3-phase 11kW with 5 m Type2 charging cable

DN-3P16-050
EAN 4016032482376



Wall-Box 3-Phase 11kW with 5m standard Charger cable

The DIGITUS Wallbox DN-3P16-050 offers an intelligent and convenient way to charge E-vehicles. The integrated connector plug (type 2) is connected to the wall-box by a 5 m long cable. Due to the IP55 protection class, a flexible installation at different locations is possible. Of course, the DN-3P16-050 wall-box is also eligible for funding by the KfW.

Homecharger / charging station, start -stop button, flexible charging cable (Type2). Input power: 11 kW.

- Charging standard: DIN EN 61851-1
- Charging power: up to 11 kW
- Rated voltage: 230 V / 400 V / AC / +/- 15%
- Connection phases: 3
- Rated current: 16 A
- Rated frequency: 50 Hz
- Vehicle charging plug: Type 2

- Dimensions: 161 × 310 × 79.8 mm (W/H/D)
- Connection: supply cable 2.5 mm² to 6 mm² - connection screwable via terminal block
- Length charging cable: 5.0 m
- Charging cable type: 3 x 2.5 mm² + 2 x 0.5 mm²
- Outer jacket: TPU
- Cable color: Black
- Operating temperature: 30°C+50°C
- Safety protection: RDC Type A + DC 6 mA (integrated)
- Protection class: IP55 (water-jet protected)
- LED status indicator: Operating and charging status
- Device protection: Emergency stop button

Package contents

- Wall-Box incl. 5 m Charger cable
- Quick Installation Guide
- Mounting kit: Clamp and screws

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	4	18.50	53.00	48.00	48.00	122,112.00
Packaging Unit Inside	1	4.63	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.63	45.00	45.00	12.00	24,300.00
Net single without Packaging	1	3.50	16.10	31.00	8.00	0.00

More images:



