

# DIGITUS USB 2.0 - USB A to Lightning Spiral Cable

AK-600433-006-S  
EAN 4016032482574



### USB Type A to Lightning Spring cable MFI C89 TPU USB 2.0, PD20W Max

With the DIGITUS® USB 2.0 - USB A to Lightning Spiral Cable, you can charge your devices with a Lightning connector. The charging power is 20W (5V/3A). In addition, you can synchronize your data with the PC or notebook at a data transfer rate of 480 Mbps. Thanks to the flexible length and spiral design, it can be used anywhere. Perfect in the car to charge your smartphone or as a spare cable for your desk, since the cable is easy to store anywhere.

### Flexible and highly robust spiral cable for charging and synchronizing - 100% MFI-certified, compatible with all Lightning devices

- Data transfer rate of up to 480 Mbps
- Supports the USB PD (Power Delivery) specification - charging power of 20W (5V/3A)
- Color cable: black
- Connector 1: Apple Lightning 8-pin, plug
- Connector 2: USB A, plug
- Connector surface: nickel-plated
- Hoods: molded
- Length: 1 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	200	6.63	44.00	51.50	29.00	65,714.00
Packaging Unit Inside	1	0.03	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.03	21.00	11.50	1.80	434.70
Net single without Packaging	1	0.03	1.00	100.00	1.00	0.00

### More images:





**AK-600433-006-S**  
USB 2.0 - USB A to Lightning Spiral Cable, 0,6m

**DIGITUS**

- 1+1 35mm Cable Length
- 1+1 1m Standing distance
- III USB charging
- III PD Fast charge function
- III Charging power

Lightning USB-A

**AK-600433-006-S**  
USB 2.0 - USB A to Lightning Spiral Cable, 0,6m

**DIGITUS**

- 1+1 35mm Cable Length
- 1+1 1m Standing distance
- III USB charging
- III PD Fast charge function
- III Charging power

Laptop Smartphone

Model	Charging Power
C48	10W
C89	12W
C94	20W

**AK-600433-006-S**  
USB 2.0 - USB A to Lightning Spiral Cable, 0,6m

**DIGITUS**

- 1+1 35mm Cable Length
- 1+1 1m Standing distance
- III USB charging
- III PD Fast charge function
- III Charging power

Model	Charging Power
C48	10W
C89	12W
C94	20W