

DIGITUS 16 Port Gigabit Ethernet Network Switch, Industrial, Unmanaged, 2 SFP Uplink

DN-651138
EAN 4016032486084



Industrial 16+2 -Port Gigabit Ethernet Switch Unmanaged, 16 RJ45 Ports 10/100/1000 Mbits

DN-651138 is a Industrial PoE Ethernet Switch with 16-Port 10/100/1000Mbps RJ45 +2 Port Gigabit SFP. The industrial graded switch has the operating temperature of -40° ~ 80°, has the super firmness can adapt to all kinds of harsh environment, can also be conveniently placed in the compact space of the control box. The installation characteristics of the guide rail, wide temperature operation, IP40 protection class housing and LED indicator light make the DN-651138 a plug and play industrial grade device, providing a reliable and convenient solution for users to network their Ethernet devices.

DN-6511318 is a industrial graded 16-port Ethernet Switch, provides non-blocking wire-speed performance in harsh industrial environment.

- 16-port 10/100/1000Base-Tx RJ-45 with auto negotiation and auto-MDI/ MDI-X function
- 2-Port SFP uplink
- -40° to 80° operating temperature
- Enclosure: IP40 aluminum housing
- Supports Air discharge: ±12kV
- Contact discharge: ±8kV
- Free Fall, Shock and Vibration Stability
- DIN-rail hardware design
- Performance Specification: Bandwidth: 52Gbps, Packet Buffer Memory: 4.1Mbit, Packet Forwarding Rate: 38.7Mpps, MAC Address Table: 8K
- Flow Control: Back pressure for half duplex, IEEE 802.3x pause frame for full duplex

- LED Indicator: Power: Red, Ethernet: Yellow
- Power Input: 12 to 57V DC redundant power
- Power Consumption: 10 watts
- Network Protocols: IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX;
- Network cables: 10BASE-T: Cat3,4,5 UTP(≤100 meter), 100BASE-TX: Cat5 or later UTP(≤100meter)
- Industry Standard: Free fall: IEC 60068-2-32; Vibration: IEC 60068-2-6
- Dimensions (W x D x H): 175.6 x 135 x 45.5 mm
- Weight: Product Weight: 1.0KGS
- Working Environment: working temperature: -40°~80° ;Storage temperature: -40°~80°
- Relative Humidity: 5%~95 % (no condensation)
- Relative humidity: 5% to max. 95% (non-condensing)
- Number of ports: 16
- Ethernet speed: Gigabit
- Industrial usage: yes
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vanadism: no
- Uplink port connection: SFP
- VLAN: no

Package contents

- 16-Port-Ethernet-Switch
- Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	12	14.00	22.50	39.00	46.50	40,803.80
Packaging Unit Inside	1	1.17	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.17	7.25	18.60	20.80	2,804.88
Net single without Packaging	1	1.00	4.60	13.50	17.60	0.00

More images:

