

DIGITUS Universal 19-Inch Equipment Rack with Castors, 8U

DN-48000
EAN 4016032490302



8U AVS rack, 420 x 507 x 460 mm threaded mounting holes, castors, bl

The 19-inch racks from DIGITUS® can be used universally thanks to their 19-inch thread perforation. Audiovisual accessories (AVS) or active and passive network components can be installed in the blink of an eye without needing captive nuts. The thread perforation of the profiles enables compatibility with US or EU screw sizes. Both screw types are included in delivery. Durable sheet steel design ensures the necessary robustness and allows maximum loads of up to 136 kg. Ventilation slits on both side walls ensure passive cooling of installation components. Equipped with rollers and carrying handles, the 19-inch racks are portable as needed for optimal positioning. Delivery is carried out as an unassembled flat pack to optimize logistics effort. The rack is easy and quick to assemble thanks to the included screwdriver and simple design. The portfolio includes various sizes to meet any requirements.

The 19-inch racks from DIGITUS® can be used universally thanks to their 19-inch thread perforation. Audiovisual accessories (AVS) or active and passive network components can be installed in the blink of an eye. Compatible with US or EU screw sizes

- 483 mm (19") thread perforation on front and back side
- Compatible with US or EU screw sizes
- Robust design made of sheet steel with load capacity up to 136 kg

- Side walls with ventilation slits for passive cooling
- Including rollers and carrying handles
- Including screwdriver and 483 mm (19") dummy cover
- Unassembled delivery as flat pack
- Product dimensions (H x W x D): 420 x 507 x 460 mm
- Product dimensions flat pack (H x W x D): 160 x 515 x 477 mm
- Weight (net/gross): 13.2 kg / 14.7 kg
- Color: Black (RAL 9005)
- Installation depth for components max.: 457,8 mm
- Cabinet type: Network cabinet
- Color: black, RAL 9005
- Front door: without
- Load capacity: 136 kg
- Side panels: Both sides
- Units: 8
- Width: 507 mm
- IP protection class: without
- Mounted: no

Package contents

- 1 x Rack
- 1 x Screwdriver
- 1 x QIG
- 1 x Set installation screws

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	13.90	54.00	49.50	13.50	36,085.50
Packaging Unit Inside	1	13.90	54.00	49.50	13.50	36,085.50
Packaging Unit Single	1	13.90	54.00	49.50	13.50	36,085.50
Net single without Packaging	1	12.80	46.00	47.70	42.00	0.00

More images:



DN-48000
Universal 19-inch Equipment Rack with Castors, 8U

Load Capacity: 100 kg
Payload Delivery: 100 kg

DN-48000
Universal 19-inch Equipment Rack with Castors, 8U

Load Capacity: 100 kg
Payload Delivery: 100 kg

DN-48000
Universal 19-inch Equipment Rack with Castors, 8U

Load Capacity: 100 kg
Payload Delivery: 100 kg

DN-48000
Universal 19-inch Equipment Rack with Castors, 8U

Load Capacity: 100 kg
Payload Delivery: 100 kg

48U with 12U* blanking cover
48U mit 12U* Blankendeckung

Side rails with ventilation slots for possible cooling
Seitenröhre mit Lüftungsschlitzen für mögliche Kühlung

Robust design made of steel sheet
with load capacity up to 100 kg
Robustes Design aus Stahlblech
mit einer Nutzlast von bis zu 100 kg

Carrying handles
Tragegriffe

Castors
Räder

DN-48000
Universal 19-inch Equipment Rack with Castors, 8U

Load Capacity: 100 kg
Payload Delivery: 100 kg