

DIGITUS 4K Wireless Video Extender, 30 m (HDMI - HDMI)

DS-55323
EAN 4016032491194



4K Wireless HDMI Extender Set, 30 m HDMI - HDMI

Experience wireless audio and video transmission in sharp UHD 4K/30Hz with the 4K Wireless HDMI Extender. The set is designed for easy setup without a driver or software thanks to Plug & Play. With a range of up to 30 meters with an unobstructed view, it guarantees reliable transmission. AES 128 encryption and the WPA2 protocol ensure secure data transmission. Compatible with HDMI 2.0/1.4 and HDCP 2.2/1.4. This is ideal for home theaters, conference rooms and training facilities. Discover the freedom of wireless entertainment!

Wirelessly transmits HDMI video and audio signals in UHD 4K/30Hz over a distance of up to 30 m with an unobstructed view

- Wireless HDMI signal transmission up to 30 m (unobstructed view)
- Point-to-point connection - 1x transmitter (source) + 1x receiver (output device)
- Supports resolutions of up to 4K UHD (2160p/30Hz)
- Easy operation and handling thanks to Plug & Play - just plug in and get started, no driver or software required
- Power supply via USB-C connection
- AES 128 bit encryption
- Authentication protocol: WPA2 (WPAS-PSK / WPA2-Enterprise)
- HDMI version: 2.0 (RX) / 1.4 (TX)
- HDCP version: 2.2 (RX) / 1.4 (TX)
- Wireless channel: IEEE 802.11.b/g/n/ac
- Frequency band: Dual Band, 2,4/5G
- Connections per unit: 1x HDMI plug, 1x USB-C jack
- Connection button with LED status display

- Power supply: Transmitter - 5V/1A, Receiver - 5V/0.6A
- Compression: H.265
- Latency: approx. 100 ms
- Audio format: PCM
- Audio channel: 2 channels
- Supports signal sources (e.g. gaming consoles, Blu-Ray players, etc.) with HDMI output as well as PCs/notebooks with Windows, macOS
- ABS housing
- Power consumption: Transmitter ca. 3W, receiver ca. 4W
- Operating temperature: 0-40 °C
- Dimensions (1 unit): L 8.1 x W 3.4 x H 1.3 cm
- Weight: Transmitter 31 g, receiver 28 g
- Color: black/silver
- The transmission distance with a restricted visual range cannot be determined generally and depends on the specific circumstances where installed
- Walls, glass etc. shorten the signal range or cause signal losses
- KVM: no
- PoE (Power over Ethernet): no

Package contents

- 1x Transmitter unit
- 1x Receiver unit
- 2x USB-A to USB-C cable (100 cm)
- 2x HDMI extension cable (12.5 cm)
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	11.70	57.00	27.00	27.00	41,553.00
Packaging Unit Inside	1	0.29	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.29	11.90	11.90	4.90	693.89
Net single without Packaging	1	0.03	8.10	3.40	1.30	0.00

More images:

