

# DIGITUS 24-Port Gigabit Netzwerkswitch, 19 Zoll, unmanaged, 2 Uplink Ports, SFP

**DN-95348-2**  
**EAN 4016032492030**



## 24-Port Gigabit + 2-Port Gigabit SFP Unmanaged PoE Switch

The DN-95348-2 PoE switch offers an outstanding solution for the efficient power supply of network components that support the IEEE802.3af/at standard. With an impressive single port output power of up to 30W, it enables the reliable supply of PoE-enabled devices. The automatic detection and identification of standard PoE receiving devices makes the power supply intelligent and prevents potential damage from non-standard or conventional devices. By prioritising the port power supply, the module ensures the module ensures a continuous power supply for critical network nodes. The panel indicators allow convenient monitoring of the working status and assist in fault analysis. The module also supports VLAN and CCTV functions to maximise flexibility in network applications. With flow control for full-duplex operation and back pressure for half-duplex operation, the module optimises data transmission efficiency. Overall, the DN-95348-2 PoE switch offers a powerful, intelligent and reliable solution for powering network components that meets today's requirements for modern network infrastructures.

## Wire-speed forwarding, intelligent identification, PoE output power of a single port supports up to 30W each, total PoE budget: 370W

- Support IEEE802.3af/at Standard
- Single port output power up to 30W
- Automatic detection and identification of standard PoE power receiving devices, intelligent power supply, will not burn non-standard PoE power receiving devices or common devices
- Support port power supply prioritization, guarantee the continuous power supply of key nodes
- Panel indicators monitor working status and help fault analysis

- Support VLAN and CCTV function
- Flow Control for Full Duplex operation and back pressure for Half Duplex Operation
- Support Energy-Efficient Ethernet (EEE) function (IEEE802.3az)
- Mainboard, Power supply, PoE (three in one)
- PoE Standard: IEEE802.3af/at
- PoE Port: Port 1~24
- PSE Power on RJ-45: Mode A 1/2(+),3/6(-)
- PoE Port Output, Voltage: 55V DC, 30W max
- PoE Power Budget: 370W
- Power supply: 400W
- Input Power Supply: AC 100-240V, 50/60Hz
- Key supply: CCTV&VLAN
- Forwarding Mode: Storage-and-Forward
- Switching Capacity: 52 Gbps
- MAC address table: 8K, Auto--learning, Auto-aging
- Jumbo frames: 9216Byte
- Packet Buffer: 4.1Mbit
- Forwarding Rate: 38,69 Mpps
- Operation Temperature: 0~40°
- Storage Temperature: -40~70°
- Operation Humidity: 10%~90% RH
- Storage Humidity: 5%~90% RH
- Dimensions(L\*W\*H): 440\*207\*44mm
- Fan Qty:2
- Industrial usage: no

## Package contents

- 24 port Gigabit PoE switch, 19 inch, unmanaged, 2 SFP uplink Power cable Quick start guide

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	3	10.70	51.00	24.00	35.00	42,840.00
Packaging Unit Inside	1	3.57	0.00	0.00	0.00	0.00
Packaging Unit Single	1	3.57	50.00	32.00	7.50	12,000.00
Net single without Packaging	1	2.73	44.00	20.80	4.40	0.00

**More images:**