

# DIGITUS CAT 6, modular couplers, shielded - 2 pieces

**AT-AG-8-8-C6S-2**  
**EAN 4016032495000**



**Modular Coupling, 8P8C, 1:1 shielded CAT6, metal housing, 2 pcs.**

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 μ
- Shielding: Tinned bronze

- PCB:FR4, UL 94V-0
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug
- 2 pieces

| Logistics                    |              |             |            |            |             |           |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
| Packaging Unit Carton        | 500          | 1.17        | 30.00      | 55.00      | 27.00       | 44,550.00 |
| Packaging Unit Inside        | 50           | 0.12        | 14.00      | 25.50      | 10.50       | 3,748.50  |
| Packaging Unit Single        | 1            | 0.00        | 3.20       | 6.00       | 3.60        | 69.12     |
| Net single without Packaging | 1            | 0.07        | 3.20       | 6.00       | 3.60        | 0.00      |

**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)