

# DIGITUS CAT 5e, Class D, RJ45 Modular Coupler - 2 pieces

DN-93901-2  
 EAN 4016032495031



**CAT 5e Modular Coupler, shielded RJ45 to RJ45, 2 pcs.**

The modular CAT5e Class D coupler from DIGITUS® consists of two shielded RJ45 female ports. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 µ
- Shielding: Tinned bronze

- PCB:FR4, UL 94V-0
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug
- 2 pieces

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	2000	18.00	51.00	27.00	25.00	34,425.00
Packaging Unit Inside	100	0.90	17.00	8.00	17.00	2,312.00
Packaging Unit Single	1	0.01	2.40	12.00	18.00	518.40
Net single without Packaging	1	0.02	7.40	2.20	4.40	0.00

**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)