

DIGITUS USB 3.0 Hub 7-Port, Industrial Line

DA-70258-1
 EAN 4016032497196



USB 3.0 HUB, 7 Port, Industrial, Metal incl. PSU 15-kV ESD, Table, Wall, DIN Rail mount

The DIGITUS® Industrial USB 3.0 Hub is ideal for industrial applications due to its metal housing. It can be mounted on the wall or on a carrier rail and is connected to a computer, notebook or server with the included USB 3.0 cable. USB 3.0 superspeed with a data transfer rate of up to 5 Gbit/s is supported, at the same time the hub is downward compatible to USB 2.0 and USB 1.1. The hub can be powered via a two-wire terminal block connector (+9V to 24V). Optionally, an external power supply can be connected to the DC jack.

Expands a computer with USB A port with 4 additional USB A super-speed ports.

- USB 3.0 metal Hub with seven downstream ports
- Battery Charging Specification BC1.2 (SDP), maximum 31.5 W (6.3 A @ 5 V)
- Power supply: +9 V to +24 V DC via terminal block or DC jack (Dimensions: (OD) 5.50mm x (ID) 2.0mm (L) x 10mm)

- Automatic detection of input polarity at the power terminal block
- ESD protection up to 15 kV for all ports
- Includes detachable wall mounting kit and DIN rail kit
- Compact industrial design with metal housing
- Weight: 304 g
- Colour: black
- Dimensions: L 13,9 x W 6,9 x H 2,5 cm
- Operating temperature: 0°C - 40°C (35°F to 100°F)

Package contents

- 1 x USB Hub
- 1 x cable USB A plug to USB B plug, length approx. 2 m
- 2 x wall mounting plates with screw package
- 1 x Top-hat rail mounting: 25 mm
- 1 x 3 pin terminal block
- 1x power supply 12V/3A
- Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	16.00	34.50	45.50	43.50	68,284.10
Packaging Unit Inside	1	0.80	33.00	44.00	20.50	29,766.00
Packaging Unit Single	1	0.80	18.40	21.00	6.20	2,395.68
Net single without Packaging	1	0.48	6.90	13.90	2.50	0.00

More images:

