


DIGITUS USB M.2 hard disk enclosure, SSD, external, NVMe + SATA, 10Gbps (NVMe) 6 Gbps (SATA), USB3.1 Gen2, aluminum, toolfree

DA-71156
EAN 4016032497561



USB hard disk enclosure, external, NVMe + SATA 10Gbps(NVMe) 6 Gbps (SATA),USB3.1 Gen2,alu,toolfre

The DA-71156 USB hard disk enclosure offers a versatile and powerful storage solution for both NVMe and SATA SSDs. With support for M.2 modules in 2230, 2242, 2260 and 2280 formats and a maximum storage capacity of up to 8 TB, it is compatible with a wide range of SSDs. The data transfer rate is 10 Gbps for NVMe and 6 Gbps for SATA, while the USB 3.1 Gen2 interface is backwards compatible with USB 3.1, 3.0, 2.0 and 1.1. The tool-free design allows for easy installation and the robust JMS581DL chipset ensures reliable and efficient performance. An integrated LED indicator makes it easy to monitor SSD status, and the durable Pantone 430C aluminum enclosure provides excellent passive heat dissipation. With compact dimensions of 101x32x10 mm and a weight of only 97 g, the housing is ideal for mobile use. It supports plug-and-play and is powered directly via the USB port. The enclosure is compatible with Windows (11, 10, 8, 7, XP, 2000), macOS, Linux (2.4.x or higher), Google Chrome OS (9.x or higher), Android and iOS and offers comprehensive support for USB-C products.

The DA-71156 M.2 SATA & NVMe SSD Enclosure will become your preferred solution for high capacity, high speed storage. This sleek, tool-less enclosure supports mini SSDs in M.2 B+M key format and offers unmatched versatility and convenience.

- Supported Mini SSD in format: M.2, M.2, B+M Key(NVMe)
- Supported storage technology: NVMe
- Max. supported capacity: 8TB

- Installation method: tool-free
- Data transfer rate: SATA: 6 Gbit/s, NVMe: 10 Gbit/s
- Supports M.2 modules in the format:2230,2242,2260,2280
- Supported keys: M Key, B+M Key (NVMe)
- USB standard: USB 3.1 Gen2
- Backwards compatible with USB: 3.1/ 3.0 / 2.0 / 1.1
- Chipset: JMS581DL
- LED activity indicator:yes
- Housing: Aluminum
- Heat dissipation: passive
- Supports Plug & Play
- Power supply via USB connection
- Supports Win 11,10, 8, 7
- Supports: Android / iOS
- Supports macOS , Linux 2.4.x or higher, Google Chrome OS 9.x or higher
- Operating temperature: 5 to 50°C
- Storage temperature: -40 to 70°C
- Humidity during operation: 5 to 90% (non-condensed)
- Dimensions: 101x32x10 mm
- Weight: 97g
- Color: Pantone 430C
- USB-C products: yes

Package contents

- External SSD enclosure, M.2 - USB Type-C™
- USB cable (C - A), 25 cm
- QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	5.00	48.00	39.50	17.00	32,232.00
Packaging Unit Inside	1	0.10	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.10	15.40	9.60	3.90	576.58
Net single without Packaging	1	0.16	12.90	1.30	5.10	0.00

More images:

