

DIGITUS USB-C docking station, 11-port

DA-70917

EAN 4016032497769



USB-C Docking Station, 11-Port, 2x HDMI, 1x DP 2x USB-A, 1x USB-C, 1x RJ45, 1x DC, 1x Audio

Expand your workplace with our USB-C docking station. Expand your screen with three external monitors thanks to the 2x HDMI ports and 1x DP port. The docking station supports both dual monitor mode (2x 4K/60Hz) and triple monitor mode (3x 4K/60Hz) in SST mode (screen mirroring) and (1x 4K/60Hz + 2x 4K/30Hz) MST mode (screen extension). Use the 2x USB-A 3.2 Gen 2 ports (10 Gbit/s) for ultra-fast data transfers, with one port also offering a 1.5A charging function for mobile devices. The USB-C 3.2 Gen 2 port (10 Gbit/s) provides extended connectivity, while the Gigabit Ethernet port (RJ45) enables a stable network connection. Two card readers (SD/MicroSD) offer a transfer speed of 104 MBps. The DC jack charges your notebook using a powerful power supply unit, and the 3.5mm audio jack rounds off the features. A reversible 100 cm USB-C connection cable ensures a flexible connection to the host. The docking station also supports DP 1.4 Alt Mode and HDR.

Our docking station offers an ideal solution for office applications - expand your notebook connections and benefit from the triple monitor function, fast data transfer and a wide range of connection options

- Connections
- 1x USB-C (3.2 Gen 2) input - Host PC connection
- 2x HDMI + 1x DP output - Max. Resolution: UHD 4K/60Hz
- 2x USB-A 3.2 Gen 2 connection - 10 Gbit/s data transfer & charging function: 1x 7.5W (5V/1.5A), 1x 4.5W (5V/0.9A)
- 1x USB-C 3.2 Gen 2 connection - 10 Gbit/s data transfer & charging function: 1x 7.5W (5V/1.5A)
- 1x RJ 45 Gigabit Ethernet connection - 10/100/1000 Mbit/s bandwidth
- 2x Card reader - 1x SD/1x MicroSD (up to 104 MBps)
- 1x DC-Jack - 150 watts max. (100W host, 50W dock)
- 1x 3.5 mm audio jack
- Anti-theft protection - 1x Standard + 1x Nano
- Chipset information: VL171, VL103R-Q4, RTL8153B, GL3224, VMM5310, VL822T, VL817-Q7S, VL162, KT0200
- Supports DP 1.4 Alt Mode, backwards compatible to DP 1.2 Alt Mode (DisplayPort Alternate Mode)
- Supports HDCP 2.2, HDCP 1.4
- Supports HDR (High Dynamic Range)
- Short-circuit, overcurrent and overvoltage protection
- Product color: Grey / Black
- Housing: aluminum / plastic
- Weight: 282 g
- Dimensions: L 18 x W 8 x H 2.3 cm
- Operating temperature : 0°C - + 45°C

- Cable length: 100 cm
- Cable color: Black
- Power switch with LED display
- Notes:
- Not all USB-C ports support all functions of the USB-C standard. Make sure that the USB-C port on your notebook supports DisplayPort Alternate Mode (DP-Alt Mode) and USB Power Delivery (PD)
- Supports dual monitor (2x 4K/60Hz) & triple monitor (1x 4K/60Hz + 2x 4K/30Hz) in MST mode (Multi Stream Transport / extend screen) - Windows, ChromeOS, Linux
- Supports dual monitor (2x 4K/60Hz) & triple monitor (3x 4K/60Hz) in SST mode (single stream transport / screen mirroring) - Windows, MacOS, iOS, iPadOS, Android, ChromeOS, Linux
- The video output capability (actual resolution) depends on the graphics card of your notebook, the connected monitor and the DP mode
- To use the full range of functions, the notebook must support DP 1.4 Alt Mode
- The docking station is not operational without a connected power supply (DC jack)
- Compatibility exists with the following operating systems up to their current versions: From Windows 7, from macOS 12, from iPhone 15 (iOS) , from iPadOS 16, from Android 14, from ChromeOS 116.0.5845.120, from Linux 22.04 LTS

Attributes

- HDTV Resolution max.: 3840 x 2160 Pixel, 60Hz
- LAN connector (RJ45): yes
- Card reader: yes
- Number of audio ports: 1
- Number of display ports: 3
- Number of network ports: 1
- Number of USB A ports: 2
- Number of USB-C ports: 1
- Number of video ports: 3
- Video connection ports: HDMI, HDMI, DisplayPort

Package contents

- 1x USB-C docking station, 11-port
- 1x QIG
- 1x USB-C cable (100 cm)
- 1x Power supply unit (21V/7,1A ; 120 cm)
- 1x Power Cord (100 cm)

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 10 | 10.70 | 31.00 | 31.00 | 23.00 | 22,103.00 |
| Packaging Unit Inside | 1 | 1.07 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 1.07 | 22.00 | 13.00 | 7.00 | 2,002.00 |
| Net single without Packaging | 1 | 0.28 | 18.00 | 8.00 | 2.30 | 0.00 |

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com