

# Ubiquiti UBNT TOUGH Cable CARRIER

UB-TOUGH-CABLE-CARRI  
EAN 0810354021336



Category 5e outdoor carrier-class shielded cable that features an Anti-Crosstalk Divider, additional shielding and is rated to provide optimal performance on Gigabit Ethernet networks.

- Cable CAT5e, Shielded
- Ethernet Support Up to 1 Gbps
- Conductor Wire Gauge 24 AWG
- Conductor Solid Bare Copper
- Conductor Diameter  $0.500 \pm 0.005$  mm
- Insulation Type Solid PE
- Insulation Thickness AVG: 0.295 mm, MIN: 0.29 mm
- Insulation Diameter  $1.16 \pm 0.02$  mm

- Separation (Polyester Wrapping) Thick: 0.025 mm, Extent: 20 mm
- Anti-Crosstalk Divider LDPE:  $4.2 \times 0.3$  mm
- Cable Shield (Aluminum Foil) Thick: 0.060 mm, Extent: 20 mm
- ESD Drain Wire 0.4 TC
- Rip Cord Yes
- Secondary Cable Shield (Braid)  $16 \times 8 \times 0.16$ AA Density: 95%
- Jacket Material PE
- Jacket Thickness AVG: 0.52 mm, MIN: 0.46 mm
- Jacket Outer Diameter  $6.8 \pm 0.30$  mm
- Jacket Color Gray
- Reference Standard ISO/IEC 11801, TIA/EIA568B.2

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	0	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00