

# Ubiquiti Ubiquiti PoE-24 power supply

**UB-POE-24-12-G**  
**EAN 0810354023002**



The Ubiquiti PoE-24 power supply features earth grounding/ESD protection and power LED.

- Output Voltage: 24VDC @ 0.5A
- Input Voltage: 90-260VAC @ 47-63 Hz
- Input Current: 0.3A @120VAC, 0.2A @230VAC
- Inrush Current: <30A peak @120VAC, <60A peak @230VAC
- Efficiency: 75+%
- Output Ripple: 1% Max
- Switching Frequency: 50kHz
- Line Regulation: +/- 1%
- Load Regulation: +/- 3%
- Operating Temperature: 0 to +40° C
- Storage Temperature: -30 to +70° C

- Operating Humidity: 35% to 95% non condensing
- Size (LxWxH): 87x84x39,2 mm
- Data IN / POE: RJ45 Shielded Socket
- Surge Protection: Difference and Common Mode
- Clamping Protection: 11V Data, 60V Power
- Max Surge Discharge: 1500A (8/20µS) Power
- Peak Pulse Current: 36A (10/1000µS) Data
- Shunt Capacitance: <5pf data
- Response Time: <1nS
- Compliance: IEC 60950-1:2005+A1, UL60950-1, EN55022:2010, EN55024:2010, FCC Class B
- Industrial usage: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.20	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.20	0.00	0.00	0.00	0.00