

Ubiquiti Ubiquiti PoE-48 power supply

UB-POE-48-G
EAN 0810354023064



The Ubiquiti PoE-48 power supply features earth grounding/ESD protection and power LED.

- Output Voltage: 48VDC @0.5A
- Input Voltage: 90-260VAC @47-63Hz
- Input Current: 0.3A @120VAC, 0.2A @230VAC
- Inrush Current: <15A peak @120VAC, <30A peak @230VAC
- Efficiency: 70+%
- Output Ripple: 1% Max
- Switching Frequency: 200kHz
- Line Regulation: +/- 0.5%
- Load Regulation: +/- 1%
- Operating Temperature: -10C to +60 deg C
- Storage Temperature: -20 to +85 deg C

- Operating Humidity: 5% to 90% non condensing
- Size (LxWxH): 85x43x30 mm
- AC Ceonector: IEC-320 C6
- Data IN / POE: RJ45 Shielded Socket
- 80% Current Indicator: Power LED will change color
- Surge Protection: Common Mode
- Clamping Protection: 11V Data, 77.5V Power
- Max Surge Discharge: 1200A (8/20uS) Power
- Peak Pulse Current: 36A (10/1000uS) Data
- Shunt Capacitance: <5pf data
- Response Time: <1nS
- Compliance: UL, EN55022 (CISPR22) class B, Meets CE
- Industrial usage: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.10	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.10	0.00	0.00	0.00	0.00