

Ubiquiti Ubiquiti UAP-AC-HD - 802.11ac Wave 2 Enterprise Wi-Fi Access Point

UB-UAP-AC-HD
EAN 0810354026126



Scalable Enterprise Wi-Fi Management: UniFi® is the revolutionary Wi-Fi system that combines enterprise performance, unlimited scalability, and a central management controller. The UniFi AC HD AP has a refined industrial design and can be easily installed using the included mounting hardware. Easily accessible through any standard web browser, the UniFi Controller software is a powerful software engine ideal for high-density client deployments requiring low latency and high uptime performance. Use the UniFi Controller software to quickly configure and administer an enterprise Wi-Fi network – no special training required. RF map and performance features, real-time status, automatic UAP device detection, and advanced security options are all seamlessly integrated. Technology: The initial 802.11ac Wave 1 SU-MIMO (Single-User, Multiple Input, Multiple Output) technology allows an earlier-generation AP to communicate with only one client at a time. The 802.11ac Wave 2 MU-MIMO (Multi-User, Multiple Input, Multiple Output) technology allows a Wave 2 AP to communicate with multiple clients at the same time – significantly increasing multi-user throughput and overall user experience. Assuming the same conditions, a Wave 2 AP provides up to 75% improvement* overall over a Wave 1 AP. This improvement increases wireless performance and/or serves more clients at the same performance level. Aggregate Multi-User TCP Throughput: 4x4 Spatial Streams: At any single time, a Wave 2 AP can communicate with the following MU-MIMO clients: Four 1x1 clients Two 2x2 clients One 2x2 client and two 1x1 clients One 3x3 client and one 1x1 client A 4x4 Wave 2 AP delivers up to 33% greater performance* than a Wave 1 AP that is 3x3 in both radio bands. Real-World Performance: The UniFi AC HD AP is the first UniFi 802.11ac Wave 2 AP. Combining the performance increases from MU-MIMO technology and the use of 4x4 spatial streams, the UniFi AC HD AP delivers up to 225% greater performance* than a typical Wave 1 AP. Client Compatibility: For optimal performance, use MU-MIMO clients. SU-MIMO clients will also benefit and gain up to 10-20% greater performance when used with the UniFi AC HD AP. * Actual performance values may vary depending on environmental and installation conditions. Hardware Overview: Deploy the UniFi AC HD AP in high-density environments requiring maximum wireless performance. The UniFi AC HD AP features simultaneous, dual-band, 4x4 MU-MIMO technology and convenient 802.3at PoE+ compatibility. Available in single- and five-packs†. Easy Mounting: Its sleek design seamlessly integrates into any environment (all accessories included) and is compatible with existing UAP-AC-PRO mounts. LED: Unique LED provisioning ring provides administrator location tracking and alerts for each device. Dual Gigabit Ethernet: The UniFi AC HD AP supports Ethernet aggregation of its Ethernet ports. Superior Processing Power:

The UniFi AC HD AP is capable of complex operations (guest control, filtering, and other resource-intensive tasks) that may slow down a lesser-equipped AP. Power over Ethernet (PoE): Includes PoE functionality. Each single-pack includes a PoE adapter. PoE Standard: The UniFi AC HD AP is compatible with an 802.3at PoE+ compliant switch. We recommend powering your UniFi devices with a UniFi PoE Switch (sold separately). UniFi PoE Switch: Available in 8, 16, 24, and 48-port versions with multiple power output options, the UniFi PoE Switch conveniently offers auto-sensing IEEE 802.3af PoE/802.3at PoE+ and configurable 24V passive PoE functionality. Each single-pack includes a PoE adapter. PoE Standard: The UniFi AC HD AP is compatible with an 802.3at PoE+ compliant switch. We recommend powering your UniFi devices with a UniFi PoE Switch (sold separately). UniFi PoE Switch: Available in 8, 16, 24, and 48-port versions with multiple power output options, the UniFi PoE Switch conveniently offers auto-sensing IEEE 802.3af PoE/802.3at PoE+ and configurable 24V passive PoE

- Dimensions: 220 x 220 x 48.1 mm (8.66 x 8.66 x 1.89")
- Weight: 700 g (1.54 lb)
- With mounting kits: 830 g (1.83 lb)
- Networking Interfaces: (2) 10/100/1000 Ethernet ports (can be aggregated)
- Port: (1) USB 3C port
- Buttons: Reset
- Power Method: Passive Power over Ethernet (48 V), 802.3at supported (supported voltage range: 44 to 57 V DC)
- Power Supply: 48 V, 0.5 A PoE Gigabit adapter*
- Power Save: Supported
- Maximum power consumption: 17 W
- TX Power:
- 2.4 GHz: 6-25 dBm
- 5 GHz: 6-25 dBm
- Antennas:
- 2.4 GHz: (2) antennas, 3 dBi each
- 5 GHz: (2) antennas, 4 dBi each
- Wi-Fi standards: 802.11 a/b/g/n/ac/ac-wave2
- Wireless security:
- WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
- 802.11w/PMF
- BSSID: Up to four per radio
- Mounting: Wall/ceiling (kits included)
- Operating temperature: -10°C to 70°C (14°F to 158°F)
- Operating humidity: 5 to 95% non-condensing
- Certifications: CE, FCC, IC

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.70	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.70	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.70	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

Discomp s.r.o
 Dopravni 1218/2a
 Plzen, Czech Republic
<https://www.discomp.cz/>
info@discomp.cz