

Ubiquiti Ubiquiti airMAX LiteBeam Gen 2 5AC 5GHz 23dBi CPE

UB-LBE-5AC-GEN2
EAN 0810354026317



The Ubiquiti Networks LBE-5AC-Gen2 is a 802.11ac LiteBeam CPE. It uses 5GHz frequencies with a 23dBi, and utilizes the new UMobile app for easy setup and installation. LiteBeam 5AC features a two-mount system that provides adjustment flexibility along both axes for versatile mounting options. The mounting system, couples with the built-in bubble level, enables quick and easy alignment.

- Dimensions: 358 x 271.95 x 272.5mm (14.09 x 10.71 x 10.73")
- Weight:
- Without Mount: 800g (1.76lbs)
- With Mount: 980g (2.16lbs)
- Power Supply: 24V, 0.3A Gigabit PoE Adapter (included)
- Max. Power Consumption: 7W
- Power Method: Passive PoE (Pairs 4,5+;7,8 Return)
- Supported Voltage Range: 24V±10%
- Operating Frequency: 2412 - 2462MHz / 5150 - 5875MHz
- Gain: 23dBi
- Networking Interface: (1) 10/100/1000 Ethernet Port
- Processor Specs: MIPS 74Kc

- Memory: 64 MB DDR2
- LEDs: Power, Ethernet
- Channel Sizes:
- PtP Mode: 10/20/30/40/50/60/80MHz
- PtMP Mode: 10/20/30/40MHz
- Enclosure Characteristics: Reflector (SGCC 0.6T) / Plastic: PC
- Mounting: Pole-Mounting Kit (Included)
- Wind Loading: 275N @ 200km/h (61.8lbf @ 125mph)
- Wind Survivability: 200km/h (125mph)
- ESD/EMP Protection: ±24kV Contact / Air
- Operating Temperature: -40 to 70°C (-40 to 158°F)
- Operating Humidity: 5 to 95% non-condensing
- Certifications: CE, FCC, IC

Package contents

- 1 x Ubiquiti LiteBeam 5AC Generation 2
- 1 x 24V/0.3A - Gigabit PoE Injector
- 1 x Quick Start Guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	1.00	0.00	0.00	0.00	0.00

More images:

