

Ubiquiti WLAN BRIDGE 5.4GHz 25dBi ISO PtP, MIMO dual pole, AC Gen2

UB-PBE-5AC-ISO-GEN2
EAN 0817882023719



The PowerBeam 5AC Gen2 ISO directional radio solution with its 6° opening angle delivers an antenna gain of up to 25dBi and a dish diameter of 460mm, making it particularly suitable for larger distances of +2km. The power is supplied via PassivePoE using the included PassivePoE power supply. It supports both PtP and PtMP and comes with a flat cover, making it ideal for harsh environments. As a special feature, the GEN2 series has an integrated 2.4GHz access point with a short range, which enables convenient commissioning via the UISP app and your smartphone.

- Data throughput: up to 450Mbps
- Dish: ISO 460mm including flat cover
- Mode: PtP and PtMP

- Installation: pole mount up to 200km/h (380N) wind load
- Power supply: 24V passive Poe max.8.5W
- Dimensions: 420x420x230mm
- Operating Temperature: -40°C ~ 70°C / Humidity: 5% ~ 95% RH
- Frequency range: 5150-5875 MHz
- Channel bandwidth: PtP: 10-80MHz / PtMP: 10-40MHz

Package contents

- 1x UB-PBE-5AC-ISO-GEN2
- Quick start guide
- Pole mounting kit
- 24V Passive PoE Injector

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	20.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	4.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

Discomp s.r.o

Dopravni 1218/2a

Plzen, Czech Republic

<https://www.discomp.cz/>

info@discomp.cz