


DIGITUS Modular plugs for flat cable

A-MO8/8SF
EAN 4016032065159



Modular Plug, for Flat Cable, 8P8C unshielded, ASS 0512 CO

These modular plugs can be used to establish quick and simple connections.

- Layout performance: CAT 3, 1GBase-T
- Area of application: Patch cable assembly
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- UL certified
- Technical properties:

- Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- Material connector body: Polycarbonat, clear
- Connector contact: Phosphor bronze, brass 0.6 μ gold-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: ≤ 20N
- Diameter Cu-Conductor: AWG (27/7 ... 24/7)
- Operating temperature: -40 °C to +80 °C
- Current carrying capacity: 1A -1.5A at 50 °C

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10000	9.30	41.30	39.00	19.50	31,408.70
Packaging Unit Inside	100	0.19	17.00	14.00	3.00	714.00
Packaging Unit Single	1000	0.00	1.50	1.00	2.50	3.80
Net single without Packaging	0	0.00	1.50	1.00	2.50	3.80