

DIGITUS Wall Mounting Cabinet Unique Series - 600x450 mm (WxD)

DN-19-07U
EAN 4016032135203



7U wall mounting cabinet, Unique 420x600x450 mm, color grey (RAL 7035)

The network cabinets for wall installation from the Unique series were developed for especially convenient and flexible network cabling. There is a sliding cable inlet with foam rubber seal in the roof of each cabinet. The back wall and floor plate are equipped with pre-cut cable inlets with a plastic cover. To accommodate a fan module, the roof structure is also equipped with a pre-cut area. Two pair of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth can be adjusted. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Removable and lockable side walls in a modular design as well as lockable and removable front door improve accessibility. The door hinges can be switched. Wall installation is accomplished in two easy work steps: The housing frame plate is bolted on the wall and then connected with the housings. With optionally available levelling feet or casters, the wall housings from the Unique series can also be used as a free-standing unit.

The DIGITUS® Unique Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Safety class rating IP20
- Lockable safety-glass door with steel frame
- 210° door opening angle
- 1-point-locking-mechanism on the front door

- Side panels are lockable and removable
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Max. installation depth: 370 mm
- Cable entry on the rear side and base with plastic cover and top with sliding cover
- Roof is prepared for fan units (punched out entries)
- Ventilation slots for active and passive ventilation and exhausting
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Rack is completely mounted
- Equipment mounting depth min.-max.: 305-370 mm
- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 450 mm
- Front door: Glass door, single opening
- Load capacity: 100 kg
- Side panels: Both sides
- Units: 7
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	18.00	50.00	65.00	47.00	152.80
Packaging Unit Inside	1	18.00	50.00	65.00	47.00	152.80
Packaging Unit Single	6	18.80	50.00	65.00	47.00	152.80
Net single without Packaging	0	17.00	45.00	60.00	42.00	113.40

More images:



DN-19 07U // Wall Mounting Cabinet Unique Series - 600x450mm

Eigenschaften
Features

- Vertikale Öffnung
Vertical opening
- Abstreifen mit Schlüssel
Lock with key
- Abstreifen
Cable entries
- Ausgewählte Lüftungsfächer
Exhaust for top and bottom
- Schraublöcher zur Montagebefähigung
Screw holes for wall mounting

Tür mit 120° Öffnungswinkel
Door with 120° opening angle

482,6mm (19") Profiltiefe, links und rechts
482,6mm (19") profile depth, left and right

DN-19 07U // Wall Mounting Cabinet Unique Series - 600x450mm

Anwendungsbeispiel
Example of use

DN-19 PRO-2 RMT
RMT 1900

Leitungen
Cables

Netzschubspann
Cable management

Wall Mounting Cabinet
Unique Series - 600 x 450 mm

DIGITUS

IP40

19" U

