

DIGITUS Hirose modular plugs TM31 for round cable, CAT 6A

A-MO6A-8/8-HRS
 EAN 4016032272144



CAT 6A modular RJ45 Plug, Hirose TM31 8P8C, shielded, for round cable, incl. hood

These modular plugs can be used to establish quick and simple connections.

- Layout performance: CAT 6A, 10GBase-T
- Area of application: Patch cable assembly
- General properties:
- Fully shielded with strain relief for installation cables
- Incl. comb
- Technical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Material connector body: Polycarbonat, clear

- Connector contact: Phosphor bronze, brass 0.8 μ gold-plated
- Material shielding housing: Brass 0.5 mm, 2 μ nickel-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: 30N max. (IEC 60603-7-5)
- Diameter Cu-Conductor: AWG (27/7 ... 24/7)
- Operating temperature: -20 °C to +60 °C
- Current carrying capacity: 1A at 50 °C
- Diameter outer jacket: 5,5 ... 6,2mm

Package contents

- 3 pieces: Plug, Cableholder, Grommet

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	600	3.70	40.00	28.00	22.00	24.60
Packaging Unit Inside	100	0.62	37.00	25.00	3.00	2.80
Packaging Unit Single	1	0.03	3.50	1.50	1.00	5.30
Net single without Packaging	0	0.03	3.00	1.50	1.00	4.50