

DIGITUS Fiber Optic Patchcord, MPO, Female, OM4, Method A, 15m

DK-2566-15/4
EAN 4016032347088



DIGITUS Fiber Optic Patchcord, MPO to MPO, Female OM4, Multimode 50/125 μ, 15m, Method A, violet

The MPO patch cable allows data rates of 40Gb/s or 100Gb/s and is the answer to the needed growing bandwidths of datacenters. The standardized IEC61754-7 and TIA/EIA 604-5 MPO Plug guaranteed the best performance in the whole network and is hardly larger than an standard RJ45 plug. The excellent damping and the compact design makes this patch cable the first choice, if we talk about bandwidth and performance.

High-performance solutions designed for efficient and scalable connectivity in data centers.

- Connector: MPO female
- Polish : PC
- Type : Method A
- Fibre type : MM 50/125 μ, OM4
- Low Insertion Fiber Count : 12
- Cable outer diameter : 3 mm
- Sheath colour : Violet

- Cable length : 15 m
- Outer sheath material : LSZH
- Max. Tensile strength : 300 N
- Min. bending radius : 30 mm
- Temperature range : -40°C till +75°C
- Cable diameter: 3 mm
- Cable jacket: LSOH
- Fiber class: OM3
- Fiber diameter: 50/125μ
- Mode: Multimode
- Number of connectors side 1: 1
- Number of connectors side 2: 1
- Number of fibers: 12
- Packaging: DIGITUS Polybag
- Length: 15 m

Package contents

- 1 x Fiber Optic Patchcord, MPO, Female, OM4, Method A, 15m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	12.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	12.00	0.00	0.00	0.00	0.00