

# DIGITUS aluminum outlet strip with pre-fuse, 8 safety outlets, 2 m supply IEC C14 plug

DN-95410  
EAN 4016032352778



**1U Aluminum PDU, rackmountable, 8x CEE 7/7 outlet 10A Plug, 250VAC 50/60Hz, IEC C14 plug, pre-fuse**

The DIGITUS® power distribution units are the perfect solution for you 482.6 mm (19") network- or server cabinet. Optimized for rack installation with 220-240V 50-60 Hz the DIGITUS® PDU offer you the best performance with qualified efficiency. The 482.6 mm (19") fixing material provides an optimized enclosing on the profile rails of your cabinets. Every PDU can be mounted horizontally as well as vertically and has the possibility, according to the cabinet, to be mounted faced up or down.

**Safe and professional power in the 482.6 mm (19") range**

- 8x safety outlets 250VAC 50/60Hz / 10A / 2500W
- Aluminum profile

- 2x angle profiles for cabinet mounting
- 2 m Cable H05VV-F 3G1,5 mm<sup>2</sup> with IEC C14 plug
- Plastic components made by ABS UL-94V-0
- Grounding on aluminium profile
- 35° turned safety outlets
- Pre-fuse
- Current: 10 A
- Input Plug: IEC 60320 C14 inlet
- Installation: Desktop, Rack 0U, Rack 1U
- Outlets: CEE 7/3
- Phase: 1ph
- Power: 2,3 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	9.64	53.00	28.50	25.00	37,762.50
Packaging Unit Inside	1	0.96	50.10	11.00	5.00	2,755.50
Packaging Unit Single	1	0.96	50.10	11.00	5.00	2,755.50
Net single without Packaging	0	0.70	46.00	4.50	4.50	931.50

**More images:**

