

DIGITUS CAT 6 S/FTP outdoor patch cord, PE

DK-1644-030/BL-OD
EAN 4016032371359



CAT 6 S-FTP outdoor patch cord, Cu, PE AWG 27/7, length 3 m, black sheath color

The DIGITUS® Category 6 Class E patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6 cabling. The performance is tested up to 250 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. With its UV resistant PE sheath, this outdoor patch cord will ensure a secure installation in areas with a lot of temperature fluctuation and sun exposure. Furthermore the drain wire will work as a lightning arrester.

Best performance and link quality for your network with UV resistance.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain reliefs and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- UV resistant, acid- & alkali resistant, corrosion resistant
- Operating temperature: -20 °C up to +60 °C
- Assortment: Twisted Pair Patch Cables
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 6
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Length: 3 m
- Color: black
- Jacket: PE
- Slim Version: no
- Structure: 4 x 2 AWG 27/7, twisted pair
- Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	60	9.10	46.00	33.00	29.00	44.00
Packaging Unit Inside	10	0.91	19.00	30.00	36.00	20.50
Packaging Unit Single	1	0.08	1.90	17.00	25.00	807.50
Net single without Packaging	0	0.08	300.00	1.20	1.30	445.80

More images:

