

# DIGITUS Internal power supply cable

**AK-430405-003-M**  
**EAN 4016032382140**



**Internal Y-power supply cable M/F/F, 0.3m, SATA 15-pin - 2x SATA 15-pin**

This cable used for the power distribution of 2 SATA-HDD's over one SATA 15-pin port of the PC power supply.

**Safe connection and power supply**

- SATA 15-pin, plug <=> 2x SATA 15-pin, jack
- Assortment: Internal Power Supply Cables
- AWG: 18

- Color cable: various
- Color connector: black
- Connector 1: SATA 15-pin plug
- Connector 2: 2x SATA 15-pin jack
- Hoods: plastic
- Wire material: CU
- Length: 0.3 m
- Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	500	26.00	45.00	34.00	28.00	42.84
Packaging Unit Inside	10	0.52	28.00	18.00	4.00	2.02
Packaging Unit Single	1	0.05	19.50	10.00	1.00	195.00
Net single without Packaging	0	0.02	105.00	8.00	1.00	840.00

**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)