

DIGITUS 2.5 SSD/HDD Enclosure, SATA I-II - USB 2.0

DA-71104 EAN 4016032391838





SSD/HDD SATA Enclosure 2.5" USB2.0, for SATA II HDD 2.5", Alu, w/o PSU

The external DIGITUS SSD/HDD hard disk enclosure gives you the flexibility to use your SSD/HDD in a modern and stylish housing. Thanks to the easy handling, a 2.5 SATA I-II SSD/HDD with a height of 9.5 or 7.0 mm is quickly installed. The slim, premium aluminum housing makes it possible for you to transport your data conveniently and to access it quickly anywhere. No additional power supply is required, power is supplied via the USB port.

External 2.5 SSD/HDD enclosure, SATA I-II to USB 2.0 with premium aluminum housing $\,$

- Supports SATA I-II SSDs/HDDs with a height of 9.5 mm or 7.0 mm
- Support capacity: up to 2 TB
- USB 2.0 data transfer rate up to 480 Mbps
- Supports hot plugging and is plug & play capable

- · Premium aluminum housing
- · Chipset: JM20329
- · Compatible with USB 2.0 specification
- LED activity indicator
- Power supply via USB (USB bus-powered)
- Supports: Windows 10, 8.1, 8, 7, Vista, XP/Mac OS 10.6 and higher
- Dimensions: L 12.2 x B 8.0 x H 1.0 cm
- Weight: 180 g
- Color: black

Package contents

- 2.5 SSD/HDD Enclosure, SATA I-II USB 2.0
- Screwdriver
- Screws
- USB 2.0 cable
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	8.50	48.00	30.00	32.00	46.08
Packaging Unit Inside	1	0.21	17.50	14.00	4.50	1,102.50
Packaging Unit Single	1	0.21	17.50	14.00	4.50	1,102.50
Net single without Packaging	0	0.18	12.00	8.00	1.00	96.00

More images:





















Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- · Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com