

DIGITUS DisplayPort connection cable with amplifier

AK-340105-100-S
EAN 4016032433699



Displayport Connection Cable, Type DP, w/ amp. M/M, 10.0m, w/lock, UHD 4K, DP 1.2, gold, bl

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

A/V connection over long distances without signal loss

- DP 1.2 Feature support
- Supports Ultra HD 4K
- Supported video formats: 4K/2K@24 Hz, 4K/2K @30 or 4K/2K 60Hz; 3D
- Supported video resolution: 4K (3840x2160)@60Hz and Full HD (1920x1080)@120Hz
- Supported audio formats: DVD-Audio, SACD, Dolby Digital Plus, TrueHD and dts-HD
- No external power supply required
- Integrated, active signal amplifier
- Supported transmission modes: RBR, HBR, HBR2

- Maximum bandwidth: 21.6 Gbps
- HBR version/transfer mode: HBR2 (5.40 Gbit/s per lane)
- HDCP version: HDCP 1.3
- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: gold-plated
- DisplayPort standard: DisplayPort 1.2
- HDTV Standard: Ultra HD 4K
- Hoods: plastic
- Interlock: Snap fastener
- Wire material: CU
- Length: 10 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	14.10	38.10	31.10	30.20	35,784.30
Packaging Unit Inside	1	1.41	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.47	33.50	33.50	5.00	5,611.30
Net single without Packaging	0	1.36	23.00	23.00	5.00	2.60

More images:

