

DIGITUS 14" Universal Notebook Docking Station, USB Type-C™

DA-70868

EAN 4016032456070



14" Universal Notebook Docking Station, USB-C 3x video, 3x USB 3.0, 2x USB-C, 2x USB 2.0, RJ45

The 14" Docking Station from DIGITUS® extends your notebook by 14 extra ports via one USB-C™ connection. It contains, inter alia, three video ports (HDMI, DisplayPort, VGA) for connecting monitors, projectors, TVs, etc. Thanks to triple monitor support, these can be used simultaneously. Under Windows, a video signal can be output simultaneously to three different video ports (SST mode); additionally, three different video signals can be output to three different graphics ports (MST mode). Mac OS supports only SST mode. The other interfaces offer connectivity to all common connections that a modern docking station should have. For example, a network connection, other USB connections (USB-C™, USB-A), an audio output or two independent card readers. The integrated USB-C™ port with PD charging can charge your notebook whilst using the docking station. The docking station also offers various USB 3.0 and 2.0 ports for data transfer, connection to periphery devices such as mouses and keyboards and for charging mobile devices. Thanks to the smart cable routing, the docking station can be connected to either side (left or right) of your notebook. Get the most out of your notebook and extend your options - all you need is one free USB-C™ connection.

The 14" docking station provides 14 additional connections for video, data, power, Ethernet and audio, inter alia, and enables you to connect it to the right or left side of your notebook thanks to its smart cable routing

- Suitable for notebooks up to 14" with a USB-C™ port, can also be used separately lying for all sizes
- Supports UHD up to 4K/30Hz to 3840 x 2160p resolution
- Triple display support - connect up to 3 monitors simultaneously
- USB-C™ version: USB 3.1 (Gen. 1)
- 1 x USB Type-C™ connection as a link to your notebook
- 1 x USB Type-C™ connection - data transfer (5 Gbps max.)
- 1 x USB Type-C™ connection - power delivery 3.0 (100 W max.)
- Power Delivery: PD 3.0 up to max. 100 W (20V/5A)
- 3 x USB 3.0 connections (data transfer 5 Gbps max.), a port with additional BC 1.2 support (max. 1.5A)
- 2 x USB 2.0 connections (480 Mbps data transfer)
- 1 x HDMI connection (max. 4K/30 Hz)
- 1 x DisplayPort connection (max. 4K/30 Hz)
- 1 x VGA connection (max. 1920 x 1200/60 Hz)
- 1 x Gigabit Ethernet connection - connect notebook to the Internet / LAN

- 2 x Card readers (microSD / SDHC, SDHX, MMC) - simultaneous use is possible
- 1 x Audio stereo jack (3.5 mm)
- Theft protection (use of a notebook lock is possible)
- Supports DisplayPort alternate mode
- DisplayPort (DP) 1.2 support
- Supports SST and MST Mode (Single Stream Transport mode / Multi Stream Transport mode)
- Three simultaneous video output signals - resolution: SST mode max. 1080p/60 Hz / MST mode max. 720p/60 Hz
- Power On / Off switch
- LED function display
- Dimensions: L 35 x W 7.4 x 1.8 cm
- Weight: 250 g
- Color: black
- Not all USB-C™ ports support all features of the USB Type-C™ standard. Make sure your notebook's USB-C™ port supports DisplayPort Alternate Mode (DP-Alt Modi) and USB Power Delivery (PD).
- The video output capability depends on the graphic card of your notebook and the connected monitor. Certain graphics cards have limited MST support, while some monitors also limit the available resolution.
- Attention: This product supports USB Type-C™ specifications, not those of Thunderbolt™ 3. Please ascertain the specifications required by your notebook in advance.
- HDTV Resolution max.: 3840 x 2160 Pixel, 30Hz
- Housing: Plastic
- LAN connector (RJ45): yes
- USB-C Power Delivery: 100W
- Card reader: yes
- Number of audio ports: 1
- Number of display ports: 3
- Number of network ports: 1
- Number of USB A ports: 3
- Number of USB-C ports: 3
- Number of video ports: 3
- USB-C Products: yes
- Video connection ports: HDMI, DisplayPort, VGA

Package contents

- 1x 14" Universal Notebook Docking Station, USB Type-C™
- 1x USB-C™ connection cable with angled plug (30 cm)
- 1 x Manual

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	12.00	40.00	44.00	26.00	45.76
Packaging Unit Inside	1	0.60	12.00	38.50	4.00	1.85
Packaging Unit Single	1	0.60	12.00	38.50	4.00	1.85
Net single without Packaging	0	0.30	7.40	35.00	1.90	492.10

More images:



**Safety notes**

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com