

# DIGITUS Variable Notebook/Tablet Stand with 6-port USB-C™ Docking Station

DA-90429 EAN 4016032482307





## Notebook Stand with USB C Hub 3x USB 3.0, 1x 4K HDMI, 1x RJ45, 1x PD Charging

The variable Notebook/Tablet Stand with 6-port USB-C™ Docking Station from DIGITUS® combines ergonomic design and connectivity. The stand enables individual height and angle adjustment, perfectly adapted to the needs of the user. The docking station offers six ports to expand the connections (1x HDMI 2.0, 3x USB-A 3.0, 1x RJ45, 1x USB-C™ PD) of your notebook/tablet. Manufactured of high-quality aluminum, the stand features elegant and modern design along with high load-bearing capacity of up to 7.5 kg, and its own weight ensures additional stability. The design of the carrier plate was conceived to ensure additional heat dissipation for notebooks.

# Individual and ergonomic adjustment options + additional connections for your notebook/tablet

- Carrier plate with heat dissipation: W 28 x D 23 cm, load-bearing capacity: 7.5 kg
- Individual height adjustment: 5.6 16.5 cm, 2x hinges each can be inclined by 180° for individual angle adjustment
- Connections Docking Station:
- 1x HDMI (4K/60Hz) connection of external monitor

- 3x USB-A 3.0/5 Gbps data transfer connection of peripheral equipment
- 1x RJ-45 Gigabit Ethernet (10/100/1000) for connection to network/internet
- 1x USB-C™ (PD 3.0) 100W max. power supply
- 1x USB-C™ 3.1 Gen. 1 host connection
- Compatible with: Windows (11/10/8/7), MacOS (10.6 or higher), iPadOS (15.3.1 or higher), Android (7.0 or higher), Chrome OS (46.0.2490.82 or higher)
- High-quality aluminum design
- Rubber pads on the carrier plate protect your devices on the stand they ensure the required stability
- USB-C™ connection cable: 60 cm
- Operating temperature: 0-40°
- Dimensions (folded together): W 28 x D 25.7 x H 5.6 cm
- Weight: 1.15 kg
- Color: Silver

### Package contents

- 1x Variable Notebook/Tablet Stand with 6-port USB-C™ Docking Station
- 1 x USB-C™ connecting cable, 60 cm
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	0	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	280.83



#### More images:





























## Safety notes

- Please read the entire manual before starting assembly and installation. Please contact your local dealer if you have any questions about the instructions or warnings.
- CAUTION: Use with products that exceed the permitted weight may result in damage or possible injury.
- Brackets should be fitted in accordance with the installation instructions. Incorrect installation can result in damage or injury.
- Use safety equipment and suitable tools. The product should only be installed by specialists.
- This product can be installed on timber-framed, solid concrete or stone walls.

  The load-bearing surfaces should be able to safely withstand the entire weight of appliances and all additional components.
- Only use the installation screws supplied and DO NOT TIGHTEN the screws TOO TIGHT.
- This product contains small parts that can cause a choking hazard if swallowed. Keep these parts away from children.
- Only use this product indoors. Using the product outdoors can lead to injuries and damage.



- IMPORTANT: Before installation, please check all components received against the components list. If parts are damaged or missing, ask your local dealer for replacement parts.
- MAINTENANCE: Check the bracket regularly for safety and stability (preferably every three months).

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com