

DIGITUS 16-Port Gigabit PoE Networkswitch, 19 Zoll, unmanaged, 2 Uplink Ports, SFP

DN-95358

EAN 4016032485445



16+2 Port GE + 2GE SFP Uplink PoE Switch 16+2 Port 10/100/1000 Mbps + 2GE SFP PoE Switch

"The DN-95358 PoE Switch is a 16-port 10/100/1000Mbps PoE + 2G Gigabit RJ45 + 2 Gigabit SFP PoE switch. The PoE ports can automatically detect IEEE 802.3af/at-compliant Powered Devices (PDs) and supply them with power. Your network is able to extend power and data transmission via a single cable to locations where there are no power lines or outlets that you could use to install devices such as APs, IP cameras or IP phones and the like. The PoE switch offers a simple, cost-effective and non-blocking wire-speed performance with 11-inch metal form for rack installation in office or department networks."

Key function: VLAN & CCTV & PD-Alive

- Interface: 16* 10/100/1000Mbps RJ45 port
- 2*10/100/1000Mbps RJ45 port
- 2*1000Mbps SFP Slot
- Standard: IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x
- Corresponds to IEEE802.3af/at Power over Ethernet
- PSE Power on RJ45: Mode A 1/2(+), 3/6(-), Mode B 4/5(+), 7/8(-)
- Supports PoE power up to 32W for each PoE port
- PoE power budget: 185W
- Energy supply: 200W
- Automatic detection of power supply device
- Remote supply of power and data up to 100 m

- Flow control for full duplex operation and back pressure for half duplex operation
- Supports VLAN and CCTV function
- 8K MAC address, automatic address learning and address aging
- Supports energy-efficient Ethernet (EEE) function IEEE802.3az
- Supports the PD alive function
- LED: PWR, PoE, LINK/ACT, PoE Max
- Maximum packet length: 8K
- Transmission mode: Store and forward
- Switching capacity: 40Gbps
- Packet forwarding rate: 29.76Mpps
- Packet buffer: 4M bit
- Fan: 1*Fan
- Weight: < 4.2Kg
- Dimensions (L*W*G): 280*180*44mm
- Industrial usage: no
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vanadism: no
- VLAN: yes

Package contents

- 16+2 Port GE + 2GE SFP Uplink PoE Switch
- Power Cord
- QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	2.58	0.00	0.00	0.00	0.00
Net single without Packaging	0	1.81	0.00	0.00	0.00	0.00

A black 8-port Ethernet switch is shown with its front panel facing the viewer. The front panel features eight RJ45 ports arranged in two rows of four. To the left of the ports are several status LEDs. To the right of the ports are two USB ports and a power input jack. A black power cord with a standard three-pronged plug is coiled next to the switch. Two black L-shaped mounting brackets and eight screws are also visible, along with two black rubber feet.

